

Specifications

: GaP
: 568 nm
: Green
: 45°
: Green Diffused
: 35


Electrical / Optical Characterisitics at TA = 25°C

Parameter	Symbol	Min	Тур	Мах	Unit	Test
Luminous Intensity	IV	20	35	50	mcd	
Viewing Angle	2⊖1/2	-	45	-	deg	
Peak Emission Wavelength	λρ	-	568	-	nm	IF = 20mA
Dominant Wavelength	λD	-	570	-	nm	1 IF = 20 mA
Spectral Line Half-Width	Δλ	-	30	-	nm	
Forward Voltage	VF	1.8	2.2	2.6	V	
Power Dissipation	Pd	-	-	85	mW	
Peak Forward Current (Duty1/10 @ 1kHz)	I⊧ (Peak)	-	-	100	mA	
Recommended Operating Current	TF (Rec)	-	10	-	mA	

Absolute Maximum Rating $T_A = 25^{\circ}C$

Reverse Voltage	5 Volt
Reverse Current	10µA (VR=5V)
Operating Temperature Range	-40°C to +85°C
Storage Temperature Range	-40°C to +100°C
Lead Soldering Temperature Range (1.6mm (1/16 inch) from body)	260°C For 5 Seconds


Typical Electro-Optical Characteristics Curves



Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



4.7mm Round With Housing Multicomp PRO



any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

