

PC CABLE, FOR PC/PG COMMUNICATION WITH SIMOCODE PRO OR SIRIUS 3RW44 SOFT STARTER OR MODULAR SAFETY SYSTEM 3RK3 VIA THE SYSTEM INTERFACE



General technical data:

<b>product brand name</b>		SIRIUS
<b>Product designation</b>		USB PC cable
<b>Design of the product</b>		<kein Wert>
<b>Protection class IP</b>		<kein Wert>
<b>Ambient temperature</b>		
• during storage	°C	-40 ... +80
• during operation	°C	-25 ... +60
• during transport	°C	-40 ... +80
<b>Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750</b>		<kein Wert>
<b>Equipment marking acc. to DIN EN 61346-2</b>		<kein Wert>

Certificates/ approvals:

General Product Approval	Test Certificates	Shipping Approval
--------------------------	-------------------	-------------------



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



GL

**other**

[PROFINET-Certification](#)

**Further information**

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrymall>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3UF79410AA000>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3UF79410AA000>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=3UF79410AA000&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3UF79410AA000&lang=en)

: