

Single-phase, primary switched mode power supply **PC-0124-200-0**



Picture shows PC-0124-200-0

Advantages

Stabilised and adjustable output voltage
Fast tripping of conventional circuit breakers
DC OK signalling
Parallel operation
Push-in terminals
Robust DIN rail mounting
Resistant to transient overvoltages up to 4 kV
3 years warranty

Applications

Power Compact combines the basic functionality of an economic switched mode power supply with key additional features to ensure high system availability. A powerful and flexible option that's still light and compact. Our real all-rounders, these power supply units are suitable for a highly diverse range of applications in solar, measurement and control technology and they really come into their own in industrial and building automation. The devices cover the average power requirement from 120 W to 480 W. Versions with 12 V, 24 V, and 48 V are available, which allow a range of applications. A version with 5 A rated current is available for a single or two-phase supply from 180 V to 550 V. The output voltage can be set easily using the rotary potentiometer on the front of the enclosure. The robust DIN rail fastening method and push-in connection terminals enable fast and secure mounting.

For applications in the medical field, power supplies are available with approval according to UL 60601-1.

Standards

Primary switched mode power supply
to UL 60950, UL 508

Safety:
EN 61558-2-16, EN 60950-1

EMC:
EN 61204-3

Approvals



UL/CSA 60950 recognised, UL508 listed, GL, EAC




Single-phase, primary switched mode power supply

PC-0124-200-0

Type	PC-0124-200-0
Electrical data	
Special features	
Characteristics	Active inrush current limit
Input	
Input rated voltage	100 - 240 Vac
Input voltage range	85 - 264 Vac (120 - 372 Vdc)
Input voltage derating	-2.5 %/Vac < 100 Vac
Rated frequency range	44 Hz - 66 Hz / 0 Hz
Input rated current (rated load)	5.56 A (100 Vac) / 2.23 A (230 Vac)
Starting current limiter	< 30 A, NTC (active)
Switch-on time	0.45 s (100 Vac) / 0.2 s (230 Vac)
Mains buffering (rated load)	20 ms (100 Vac) / 20 ms (230 Vac)
Power factor	0.98 (active PFC)
Input fuse internal	10 A
Recommended back-up fuse (circuit breaker)	10 A, 16 A, characteristic B, C
Transient surge voltage protection	Varistor
Output	
Output rated voltage	24 Vdc
Output voltage range	23 - 28,5 Vdc
Output rated current	20 A
Output limited current	typ. 22 A (constant current)
Tripping of LS circuit breakers	max. B6, C6, K4
Parallel connection	Yes
Serial operation	Yes
Power dissipation, no load/rated load	7.2 / 42.4 W (230 Vac)
Max. power losses	68.3 W (100 Vac / 24 V / 20 A)
Efficiency	typ. 92 %
Ripple factor	typ. 70 mVss
Resistance to reverse feed max.	35 Vdc
Over-voltage-protection	max. 40 Vdc
Signaling	
Typ. switching threshold for LED and signal output (DC OK)	-
Status indicator	LED green
Signal output	Relay contact
Approvals	
Approvals	cURus, cULus, GL, EAC
Environment	
Type of cooling	natural convection
Ambient temperature	-25 °C to +70 °C
Storage temperature	-25 °C to +85 °C
Derating	-5 %/K > +60 °C @ 196 - 264 Vac -2.5 %/K > +50 °C @ 85 - 195 Vac
Required minimum spacing (left/right)	0 mm
Required minimum spacing (over/under)	50 mm
Safety and protection	
Protection index	IP 20
Safety class	I, with PE connection
Order numbers	
Order Number	PC-0124-200-0

Type	PC-0124-200-0
Mechanical data	
Environment	
Mounting position	horizontal for standard rail DIN TS35
Terminal and mounting	
Terminals signalling (direct plug-in technology Push-in)	max. 2,5 mm ²
Terminals input (direct plug-in technology Push-in)	max. 2,5 mm ²
Terminals output (direct plug-in technology Push-in)	max. 6 mm ²
Measures and weights	
Weight	1.60 kg



Subject to change.