217


# 5x20mm panel mounting fuseholders


#### **Product overview**


- Finger/screwdriver release
- · Anti-rotation key fixing
- · Combined solder/2.8mm quick connect terminals
- Compact
- EN60127
- . c¶us,♠, C€ approved



SPECIFICATION	
Rating	10A/250V
Contacts	Tinned nickel plated brass
Moulding	UL94-V0 flame retardant PC
Dielectric strength	>3kV
Insulation resistance	>101MΩ
Power dissipation	2.5W
Operating temperature	-30°C to +85°C







### **KEY FEATURES**

Finger or screw release | Anti rotation | Standard profile panel mount

## 5x20mm snap fit panel mounting fuseholders


### **Product overview**


- · Snap-fit panel mounting
- · Screwdriver release screw fuse carrier
- · Combined solder/2.8mm quick connect terminals
- · Anti-rotation D fixing
- EN60127
- . c¶us,♠, C€ approved



SPECIFICATION	
Rating	6.3A/ 250V
Contacts	Tinned nickel plated brass
Moulding	UL94-V0 flame retardant PBT
Dielectric strength	3kV
Insulation resistance	>100MΩ
Power dissipation	2.5W
Operating temperature	-30°C to +85°C

PART NO.	CARRIER	RELEASE
CFH08	Screw	Screwdriver





### **KEY FEATURES**

Hybrid terminal | Anti rotation body moudling | quick release carrier