

1

2

3

4

5



TECHNICAL CHARACTERISTICS

MATERIAL
INSULATOR: PBT
FLAMMABILITY RATING: UL94V0
COLOR: BLACK

ENVIRONMENTAL
OPERATING TEMPERATURE: -40°C UP TO +125°C
COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL
WITHSTANDING VOLTAGE: 500 VAC/MIN
INSULATION RESISTANCE: >1000 MΩ



PACKAGING
BOX



$$A = (\text{nb. pin}-1) \times \text{pitch}$$

$$B = (\text{nb. pin} \times \text{pitch})$$

RoHS Compliant

G				PROJECTION: 	GENERAL TOLERANCE $\pm 0,1$		DESCRIPTION: 2.54 MM INTERCOM SINGLE ROW FEMALE TERMINAL HOUSING	SIZE A4
F								
E								
D								
C	17-JUN-16	DESCRIPTION	AK	APPROVAL: BBu	UNIT: MM	WERI PART NO: 661 0xx 113 322		
B	20-OCT-15	UPDATE	AK		SCALE:			
A	22-SEP-14	PDF	AK		SHEET: 1/2			
REV	DATE	FILE	BY		DRAW: AK			

1

2

3

4

5

Cautions and Warnings:

This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Würth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

A

B

C

RoHS Compliant

G				PROJECTION: 	GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15		
F							
E							
D							
C				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE A4
B					SCALE:		
A	10-SEP-14	PDF	QL		SHEET: 2/2	WERI PART NO: DISCLAIMER	
REV	DATE	FILE	BY		DRAW: QL		

D