

## ANT-M4G3-SMA

### Features

- Frequency Range
  - 690-960
  - 1710-2170
  - 2400-2700MHz
- Omni Directional 3 dBi Gain
- Rugged plastic finish IP65 Rated.
- Wall Mount Bracket
- 50ohm Impedance
- 3m RG58U with SMA Male
- Vertical Polarization
- V.S.W.R  $\leq$ 2.5
- 270mm Long
- Operating Temp  $-30^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$



### Applications

- 4G / LTE Applications
- GSM Applications
- WiFi


### Description

A wall mount LTE and GSM antenna supplied with a 3m RG58U cable and male SMA connector. This ready to operate antenna required no tuning and provides optimum range and reliability to your application.

### Ordering Information

Part No	Description
ANT-M4G3-SMA	4G LTE/GSM Outside antenna (IP65 Rated) with SMA Male Connector

## Mechanical Drawing



All Dimensions in mm



RF Antenna for LTE and GSM Applications


**NOT TO SCALE**

REV	DESCRIPTION	DATE	APPROVED
1	First Issue	18/07/16	
2			
3			
4			
5			
6			

## V.S.W.R Test Report




## S11 Test Report



## 2D Pattern—E Plane 824MHz: 1.81917 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-E.nsi




```

Far-field amplitude, E-principal: Linear, Ytu = 0.000 deg
Gain = 1.81917 dBi
Max far-field (global) = -41.18017 dB, Max far-field (plot) =
-42.18021 dB
Normalization: Reference, Network offset = 0.880 dB
Vpeak at: -100.00001 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-E
NI22080 V4.9.124, Filename:C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-E.nsi
Measurement date/time: 7/1/2015 3:51:23 PM, Filetype: NLI-97
Far-field Cut Analysis:
Avg value: -4.244 dB
-3. dB beam width: 22.53 deg
-6. dB beam width: 36.14 deg
-16. dB beam width: 100.16 deg
Left Side-lobe: Not Found
Right Side-lobe: -15.64 dB at 25.140 deg
Far-field display setup
Azimuth (deg)
Span = 260.00001 deg, Center = 0.000 deg, #pts = 101
Start = -150.00001 deg, Stop = 150.00001 deg, Delta = 2.069
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
----
2 0.824 GHz Azimuth Elevation Single-pol
    
```

## 2D Pattern—E Plane 850MHz: 0.84165 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-E.nsi




```

Far-field amplitude, E-principal: Linear, Ytu = 0.000 deg
Gain = 0.84165 dBi
Max far-field (global) = -40.41521 dB, Max far-field (plot) =
-40.41523 dB
Normalization: Reference, Network offset = 0.880 dB
Vpeak at: -100.000 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-E
NI22080 V4.9.124, Filename:C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-E.nsi
Measurement date/time: 7/1/2015 3:51:23 PM, Filetype: NLI-97
Far-field Cut Analysis:
Avg value: -6.448 dB
-3. dB beam width: 21.87 deg
-6. dB beam width: 32.59 deg
-16. dB beam width: 92.00 deg
Left Side-lobe: Not Found
Right Side-lobe: -28.76 dB at -29.162 deg
Far-field display setup
Azimuth (deg)
Span = 260.00001 deg, Center = 0.000 deg, #pts = 101
Start = -150.00001 deg, Stop = 150.00001 deg, Delta = 2.069
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
----
3 0.850 GHz Azimuth Elevation Single-pol
    
```

## 2D Pattern—E Plane 900MHz: 1.72636 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-E.nsi




```

Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = 1.72636 dBi
Max far-field (global) = -39.83332 dB, Max far-field (plot) =
-39.83333 dB
Normalization: Reference, Network offset = 0.180 dB
Hpeak at: -180.00001 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-00 ANT+CALBE-3.5M-E
N522080 V4.0.124, Filename:C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-E.nsi
Measurement date/time: 7/1/2015 3:51:23 PM, Filetype: N5I-97
Far-field Cut Analysis:
Avg values: -1.326 dB
-1. dB beam width: 67.34 deg
-6. dB beam width: 66.05 deg
-10. dB beam width: 82.91 deg
Left sidelobe: Not Found
Right sidelobe: -9.33 dB at -65.251 deg
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 181
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
----
4 0.900 GHz Azimuth Elevation Single-pol
    
```

## 2D Pattern—E Plane 960MHz: 1.60164 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-E.nsi




```

Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = 1.60164 dBi
Max far-field (global) = -41.82803 dB, Max far-field (plot) =
-41.82805 dB
Normalization: Reference, Network offset = 0.060 dB
Hpeak at: -180.00000 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-E
N522080 V4.0.124, Filename:C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-E.nsi
Measurement date/time: 7/1/2015 3:51:23 PM, Filetype: N5I-97
Far-field Cut Analysis:
Avg values: -4.728 dB
-1. dB beam width: 41.05 deg
-6. dB beam width: 51.00 deg
-10. dB beam width: 72.67 deg
Left sidelobe: Not Found
Right sidelobe: -2.56 dB at -49.274 deg
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 181
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
----
5 0.960 GHz Azimuth Elevation Single-pol
    
```

## E-Plane 1710MHz: 1.06143 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-E.nsi



```


Far-field amplitude, E-principal: Linear, Tau = 0.000 deg
Gain = 1.06143 dBi
Max far-field (global) = -44.13116 dB, Max far-field (plot) =
-44.13123 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: 128.900 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-E
NSI2000 V4.0.324, Filename: C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-E.nsi
Measurement date/time: 7/1/2015 3:51:23 PM Filetype: NSI-97
Far-field Cut Analysis:
Avg value: -4.254 dB
-1. dB beam width: 38.87 deg
-6. dB beam width: 45.75 deg
-10. dB beam width: 59.20 deg
Left side-lobe: -2.99 dB at 103.375 deg
Right side-lobe: Not Found
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 182
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1

Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
----
1 1.710 GHz Azimuth Elevation Single-pol
    
```

## E-Plane 1800MHz: 1.76763 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-E.nsi



```


Far-field amplitude, E-principal: Linear, Tau = 0.000 deg
Gain = 1.76763 dBi
Max far-field (global) = -45.85441 dB, Max far-field (plot) =
-45.85440 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: 128.900 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-E
NSI2000 V4.0.324, Filename: C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-E.nsi
Measurement date/time: 7/1/2015 3:51:23 PM Filetype: NSI-97
Far-field Cut Analysis:
Avg value: -3.262 dB
-1. dB beam width: 21.47 deg
-6. dB beam width: 41.10 deg
-10. dB beam width: 59.37 deg
Left side-lobe: -2.05 dB at 105.507 deg
Right side-lobe: Not Found
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 182
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1

Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
----
10 1.800 GHz Azimuth Elevation Single-pol
    
```

## E-Plane 1900MHz: 0.96073 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-E.nsi



```

Far-field amplitude, E-principal: Linear, Tau = 0.000 deg
Gain = 0.96073 dBi
Max far-field (global) = -46.97623 dB, Max far-field (plot) =
-46.97623 dB
Normalization: Reference, Network offset = 0.000 dB
Rpeak at: 141.99999 deg, Vpeak at: 0.000 deg
Plot centering: on


20150701-4G ANT+CALBE-3.5M-E

NI2200 V4.0.124, Filename: C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-E.nsi
Measurement date/time: 7/1/2015 3:51:23 PM, Filetype: NII-97
Far-field Cut Analysis:
Avg value: -4.289 dB
-1. dB beam width: 21.40 deg
-2. dB beam width: 21.25 deg
-10. dB beam width: 48.59 deg
Left side-lobe: -1.40 dB at 109.609 deg
Right side-lobe: Not found
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 181
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1

Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
----
11 1.900 GHz Azimuth Elevation Single-pol
    
```

## E-Plane 2170MHz: 0.72134 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-E.nsi



```

Far-field amplitude, E-principal: Linear, Tau = 0.000 deg
Gain = 0.72134 dBi
Max far-field (global) = -46.91077 dB, Max far-field (plot) =
-46.91077 dB
Normalization: Reference, Network offset = 0.000 dB
Rpeak at: 42.99999 deg, Vpeak at: 0.000 deg
Plot centering: on


20150701-4G ANT+CALBE-3.5M-E

NI2200 V4.0.124, Filename: C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-E.nsi
Measurement date/time: 7/1/2015 3:51:23 PM, Filetype: NII-97
Far-field Cut Analysis:
Avg value: -5.247 dB
-1. dB beam width: 45.11 deg
-2. dB beam width: 32.49 deg
-10. dB beam width: 110.41 deg
Left side-lobe: -1.27 dB at -57.210 deg
Right side-lobe: -0.77 dB at 87.486 deg
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 181
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1

Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
----
12 2.170 GHz Azimuth Elevation Single-pol
    
```

## E-Plane 2400MHz: 1.73269 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-E.nsi




```

Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = 1.73269 dBi
Max far-field (global) = -47.27494 dB, Max far-field (plot) =
-47.27496 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: -54.000 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-E
NSI2000 V4.0.124, Filename: C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-E.nsi
Measurement date/time: 7/1/2015 3:51:23 PM, Filetype: NSI-97
Far-field Cut Analysis:
Avg value: -4.254 dB
-1. dB beam width: 21.86 deg
-6. dB beam width: 44.51 deg
-10. dB beam width: 57.59 deg
Left side-lobe: -11.48 dB at -92.520 deg
Right side-lobe: -0.06 dB at 47.203 deg
Far-field display setup
Azimuth (deg)
Span = 268.00001 deg, Center = 0.000 deg, #pts = 181
Start = -190.00001 deg, Stop = 190.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
-----
12 2.400 GHz Azimuth Elevation Single-pol
    
```

## E-Plane 2500 MHz: 1.04758 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-E.nsi



```


Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = 1.04758 dBi
Max far-field (global) = -49.88841 dB, Max far-field (plot) =
-49.88846 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: -60.00001 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-E
NSI2000 V4.0.124, Filename: C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-E.nsi
Measurement date/time: 7/1/2015 3:51:23 PM, Filetype: NSI-97
Far-field Cut Analysis:
Avg value: -4.572 dB
-1. dB beam width: 28.25 deg
-6. dB beam width: 29.90 deg
-10. dB beam width: 59.99 deg
Left side-lobe: -2.43 dB at -125.699 deg
Right side-lobe: -11.55 dB at 3.917 deg
Far-field display setup
Azimuth (deg)
Span = 268.00001 deg, Center = 0.000 deg, #pts = 181
Start = -190.00001 deg, Stop = 190.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
-----
14 2.500 GHz Azimuth Elevation Single-pol
    
```



## E-Plane 2600MHz: 2.59262 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-E.nsi




```

Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = 2.59262 dBi
Max far-field (global) = -47.72417 dB, Max far-field (plot) =
-47.72429 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: -156.000 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-E
N32300 V4.0.124, Filename: C:\Documents and Settings\N31\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-E.nsi
Measurement date/time: 7/1/2015 3:51:23 PM, Filetype: NSI-57
Far-field Cut Analysis:
Avg value: -4.167 dB
-1. dB beam width: 23.08 deg
-6. dB beam width: 46.20 deg
-10. dB beam width: 76.30 deg
Left sidelobe: Not Found
Right sidelobe: -11.26 dB at -191.564 deg
Far-field display setup
Azimuth (deg)
Span = 269.00001 deg, Center = 0.000 deg, #pts = 181
Start = -190.00001 deg, Stop = 190.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
-----
1 2.600 GHz Azimuth Elevation Single-pol
    
```

## H-Plane 806MHz: 1.37841 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-H.nsi




```

Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = 1.37841 dBi
Max far-field (global) = -41.30906 dB, Max far-field (plot) =
-41.30906 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: -60.00001 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-H
N32300 V4.0.124, Filename: C:\Documents and Settings\N31\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-H.nsi
Measurement date/time: 7/1/2015 3:36:28 PM, Filetype: NSI-57
Far-field Cut Analysis:
Avg value: -0.077 dB
-1. dB beam width: Not Found
-6. dB beam width: Not Found
-10. dB beam width: Not Found
Left sidelobe: Not Found
Right sidelobe: -0.91 dB at 59.330 deg
Far-field display setup
Azimuth (deg)
Span = 269.00001 deg, Center = 0.000 deg, #pts = 181
Start = -190.00001 deg, Stop = 190.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
-----
1 0.806 GHz Azimuth Elevation Single-pol
    
```

## H-Plane 824MHz: 1.77902 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-H.nsi




```

Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = 1.77902 dBi
Max far-field (global) = -41.22032 dB, Max far-field (plot) =
-41.22032 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: -69.000 deg, Vpeak at: 0.000 deg
Plot centering: On
20150701-4G ANT+CALBE-3.5M-H
N522000 V4.0.124, Filename: C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-H.nsi
Measurement date/time: 7/1/2015 3:36:20 PM, Filetype: NSI-97
Far-field Cut Analysis:
Avg value: 0.271 dB
-1. dB beam width: Not Found
-6. dB beam width: Not Found
-10. dB beam width: Not Found
Left Sidelobe: Not Found
Right Sidelobe: Not Found
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 181
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
-----
2 0.824 GHz Azimuth Elevation Single-pol
    
```

## H-Plane 850 MHz: -1.60185 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-H.nsi




```

Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = -1.60185 dBi
Max far-field (global) = -42.85071 dB, Max far-field (plot) =
-42.85071 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: -76.00001 deg, Vpeak at: 0.000 deg
Plot centering: On
20150701-4G ANT+CALBE-3.5M-H
N522000 V4.0.124, Filename: C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-H.nsi
Measurement date/time: 7/1/2015 3:36:20 PM, Filetype: NSI-97
Far-field Cut Analysis:
Avg value: -2.107 dB
-1. dB beam width: Not Found
-6. dB beam width: Not Found
-10. dB beam width: Not Found
Left Sidelobe: Not Found
Right Sidelobe: -0.24 dB at 87.486 deg
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 181
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
-----
2 0.850 GHz Azimuth Elevation Single-pol
    
```

## H-Plane 900MHz: -2.47165 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-H.nsi




```

Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = -2.47165 dBi
Max far-field (global) = -44.93133 dB, Max far-field (plot) =
-44.93134 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: -62.90001 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-H
NSI2008 V4.0.324, Filename: C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-H.nsi
Measurement date/time: 7/1/2015 3:36:28 PM, Filetype: NSI-97
Far-field Cut Analysis:
Avg values: -1.539 dB
-1. dB beam width: 121.69 deg
-6. dB beam width: Not Found
-10. dB beam width: Not Found
Left side-lobe: Not Found
Right side-lobe: -0.95 dB at 37.207 deg
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 181
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
-----
4 0.900 GHz Azimuth Elevation Single-pol
    
```

## H-Plane 960MHz: -3.26146 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-H.nsi




```

Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = -3.26146 dBi
Max far-field (global) = -45.89113 dB, Max far-field (plot) =
-45.89114 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: 19.59999 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-H
NSI2008 V4.0.324, Filename: C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-H.nsi
Measurement date/time: 7/1/2015 3:36:28 PM, Filetype: NSI-97
Far-field Cut Analysis:
Avg values: -3.182 dB
-1. dB beam width: 143.18 deg
-6. dB beam width: Not Found
-10. dB beam width: Not Found
Left side-lobe: -3.19 dB at -105.397 deg
Right side-lobe: Not Found
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 181
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
-----
5 0.960 GHz Azimuth Elevation Single-pol
    
```

## H-Plane 1710MHz -1.21375 dBi


Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-H.nsi



Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg  
 Gain = -1.21375 dBi  
 Max far-field (global) = -46.40634 dB, Max far-field (plot) =  
 -46.40628 dB  
 Normalization: Reference, Network offset = 0.000 dB  
 Rpeak at: -164.000 deg, vpeak at: 0.000 deg  
 Plot centering: 0e  
 20150701-4G ANT+CALBE-3.5M-H  
 NSI2006 V4.0.124, Filename: C:\Documents and Settings\MSI\Desktop\20  
 150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-H.nsi  
 Measurement date/time: 7/1/2015 3:36:28 PM, Filetype: NSI-97  
 Far-field Cut Analysis:  
 Avg value: -3.684 dB  
 -1. dB beam width: Not Found  
 -6. dB beam width: Not Found  
 -10. dB beam width: Not Found  
 Left Sidelobe: Not Found  
 Right Sidelobe: -1.87 dB at -133.631 deg  
 Far-field display setup  
 Azimuth (deg)  
 Span = 360.00001 deg, Center = 0.000 deg, #pts = 181  
 Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000  
 deg  
 Elevation (deg)  
 Center = 0.000 deg, #pts = 1  
 Selected beam(s) 1 of 15  
 Beam Frequency Azimuth Elevation Pol  
 ---  
 9 1.710 GHz Azimuth Elevation Single-pol

## H-Plane 1800MHz: 0.29161 dBi


Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-H.nsi



Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg  
 Gain = 0.29161 dBi  
 Max far-field (global) = -46.53043 dB, Max far-field (plot) =  
 -46.52648 dB  
 Normalization: Reference, Network offset = 0.000 dB  
 Rpeak at: 73.99999 deg, vpeak at: 0.000 deg  
 Plot centering: 0e  
 20150701-4G ANT+CALBE-3.5M-H  
 NSI2006 V4.0.124, Filename: C:\Documents and Settings\MSI\Desktop\20  
 150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-H.nsi  
 Measurement date/time: 7/1/2015 3:36:28 PM, Filetype: NSI-97  
 Far-field Cut Analysis:  
 Avg value: -3.447 dB  
 -1. dB beam width: 23.46 deg  
 -6. dB beam width: 50.52 deg  
 -10. dB beam width: Not Found  
 Left Sidelobe: -2.12 dB at 125.098 deg  
 Right Sidelobe: -4.62 dB at 125.098 deg  
 Far-field display setup  
 Azimuth (deg)  
 Span = 360.00001 deg, Center = 0.000 deg, #pts = 181  
 Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000  
 deg  
 Elevation (deg)  
 Center = 0.000 deg, #pts = 1  
 Selected beam(s) 1 of 15  
 Beam Frequency Azimuth Elevation Pol  
 ---  
 10 1.800 GHz Azimuth Elevation Single-pol

## H-Plane 1900MHz: -0.03944 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-H.nsi




```

Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = -0.03944 dBi
Max far-field (global) = -47.9764 dB, Max far-field (plot) =
-47.9764 dB
Normalization: Reference, Network offset = 0.080 dB
Vpeak at: 85.9999 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-H
NSI2000 V4.0.124, Filename:C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-H.nsi
Measurement Date/Time: 7/1/2015 3:36:20 PM, Filetype: NSI-97
Far-field Cut Analysis:
Avg value: -2.231 dB
-3. dB beam width: 37.22 deg
-6. dB beam width: Not Found
-10. dB beam width: Not Found
Left Sidelobe: -8.27 dB at 37.287 deg
Right Sidelobe: Not Found
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 181
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
----
11 1.900 GHz Azimuth Elevation Single-pol
    
```

## H-Plane 2170MHz: 0.020 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-H.nsi




```

Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = 0.020 dBi
Max far-field (global) = -47.51211 dB, Max far-field (plot) =
-47.51212 dB
Normalization: Reference, Network offset = 0.080 dB
Vpeak at: 29.9999 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-H
NSI2000 V4.0.124, Filename:C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-H.nsi
Measurement Date/Time: 7/1/2015 3:36:20 PM, Filetype: NSI-97
Far-field Cut Analysis:
Avg value: -0.759 dB
-3. dB beam width: Not Found
-6. dB beam width: Not Found
-10. dB beam width: Not Found
Left Sidelobe: -8.09 dB at -51.285 deg
Right Sidelobe: Not Found
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 181
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
----
12 2.170 GHz Azimuth Elevation Single-pol
    
```

## H-Plane 2400MHz –6.23579 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-H.nsi



```


Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = -6.23579 dBi
Max far-field (global) = -55.24242 dB, Max far-field (plot) =
-55.24246 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: 57.99999 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-H
NSI2000 V4.0.124, Filename: C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-H.nsi
Measurement date/time: 7/1/2015 3:36:28 PM, Filetype: NSI-97
Far-field Cut Analysis:
Avg value: -9.108 dB
-3. dB beam width: 28.34 deg
-6. dB beam width: 245.17 deg
-10. dB beam width: Not Found
Left Sidelobe: -9.32 dB at -21.117 deg
Right Sidelobe: -1.24 dB at 97.542 deg
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 181
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1

Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
---
12 2.400 GHz Azimuth Elevation Single-pol
    
```

## H-Plane 2500MHz: -8.61832 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-H.nsi



```


Far-field amplitude, Eprincipal: Linear, Tau = 0.000 deg
Gain = -8.61832 dBi
Max far-field (global) = -59.75431 dB, Max far-field (plot) =
-59.75436 dB
Normalization: Reference, Network offset = 0.000 dB
Hpeak at: 78.99999 deg, Vpeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-H
NSI2000 V4.0.124, Filename: C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-H.nsi
Measurement date/time: 7/1/2015 3:36:28 PM, Filetype: NSI-97
Far-field Cut Analysis:
Avg value: -17.450 dB
-3. dB beam width: 21.28 deg
-6. dB beam width: 87.42 deg
-10. dB beam width: 99.70 deg
Left Sidelobe: -2.09 dB at 42.240 deg
Right Sidelobe: -0.07 dB at 107.599 deg
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 181
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1

Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
---
14 2.500 GHz Azimuth Elevation Single-pol
    
```

## H-Plane 2600MHz: -7.49977 dBi

Far-field amplitude of 20150701-4G ANT+CALBE-3.5M-H.nsi



```
Far-field amplitude, E-principal: Linear, Tau = 0.000 deg
Gain = -7.49977 dBi
Max far-field (global) = -57.93000 dB, Max far-field (plot) =
-57.91600 dB
Normalization: Reference, Network offset = 0.000 dB
Ypeak at: 117.99999 deg, Ypeak at: 0.000 deg
Plot centering: On

20150701-4G ANT+CALBE-3.5M-H

NSI2000 V4.0.124, Filename: C:\Documents and Settings\NSI\Desktop\20
150701-4G ANT+CALBE-3.5M\20150701-4G ANT+CALBE-3.5M-H.nsi
Measurement date/time: 7/1/2015 3:26:28 AM, Filetype: NSI-97
Far-field Cut Analysis:
Avg value: -15.671 dB
-3. dB beam width: 44.15 deg
-6. dB beam width: 52.56 deg
-10. dB beam width: 62.50 deg
Left sidelobe: -7.01 dB at 61.341 deg
Right sidelobe: -10.84 dB at 153.855 deg
Far-field display setup
Azimuth (deg)
Span = 360.00001 deg, Center = 0.000 deg, #pts = 181
Start = -180.00001 deg, Stop = 180.00001 deg, Delta = 2.000
deg
Elevation (deg)
Center = 0.000 deg, #pts = 1
Selected beam(s) 1 of 15
Beam Frequency Azimuth Elevation Pol
15 2.600 GHz Azimuth Elevation Single-pol
```

### RF Solutions Ltd. Recycling Notice Meets the following EC Directives:

#### DO NOT

Discard with normal waste, please recycle.

#### ROHS Directive 2002/95/EC

Specifies certain limits for hazardous substances.

#### WEEE Directive 2002/96/EC

Waste electrical & electronic equipment. This product must be disposed of through a licensed WEEE collection point. RF Solutions Ltd., fulfills its WEEE obligations by membership of an approved compliance scheme.

#### Disclaimer:

Whilst the information in this document is believed to be correct at the time of issue, RF Solutions Ltd does not accept any liability whatsoever for its accuracy, adequacy or completeness. No express or implied warranty or representation is given relating to the information contained in this document. RF Solutions Ltd reserves the right to make changes and improvements to the product(s) described herein without notice. Buyers and other users should determine for themselves the suitability of any such information or products for their own particular requirements or specification(s). RF Solutions Ltd shall not be liable for any loss or damage caused as a result of user's own determination of how to deploy or use RF Solutions Ltd's products. Use of RF Solutions Ltd products or components in life support and/or safety applications is not authorised except with express written approval. No licences are created, implicitly or otherwise, under any of RF Solutions Ltd's intellectual property rights. Liability for loss or damage resulting or caused by reliance on the information contained herein or from the use of the product (including liability resulting from negligence or where RF Solutions Ltd was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict RF Solutions Ltd's liability for death or personal injury resulting from its negligence.

### Waste Batteries and Accumulators Directive 2006/66/EC

Where batteries are fitted, before recycling the product, the batteries must be removed and disposed of at a licensed collection point.

Environment Agency producer registration number: WEE/JB0104WV.