SIEMENS

Data sheet 3TY7561-1AA00

AUXILIARY CONTACT BLOCK AUX. CONTACT BLOCK LEFT 1NO1NC

| General technical data: | General technical data: | | | | |
|---|-------------------------|-------------------------------------|--|--|--|
| Suitability for use | | Contactor relay and power contactor | | | |
| Protection class IP on the front | | IP20 | | | |
| Ambient temperature | | | | | |
| during storage | °C | -55 + 80 | | | |
| during operation | °C | -25 + 55 | | | |
| Mechanical service life (switching cycles) typical | | 10 000 000 | | | |
| Insulation voltage with degree of pollution 3 Rated value | V | 690 | | | |
| Surge voltage resistance Rated value | kV | 6 | | | |
| Auxiliary circuit: | | | | | |
| Number of NC contacts for auxiliary contacts | | | | | |
| • instantaneous contact | | 1 | | | |
| lagging switching | | 0 | | | |
| Number of NO contacts for auxiliary contacts | | | | | |
| instantaneous contact | | 1 | | | |
| leading contact | | 0 | | | |
| Operating current of the auxiliary contacts at AC-12 | | | | | |
| ● at 24 V | Α | 10 | | | |
| ● at 230 V | Α | 10 | | | |
| • maximum | Α | 10 | | | |
| Operating current | | | | | |
| of the auxiliary contacts | | | | | |
| — at AC-14 | | | | | |
| — at 125 V | Α | 10 | | | |
| — at AC-15 | | | | | |
| — at 24 V | Α | 10 | | | |
| — at 230 V | Α | 5.6 | | | |
| — at 400 V | Α | 3.6 | | | |
| • at AC-15 at 690 V Rated value | Α | 2.3 | | | |
| Operating current | | | | | |
| • of the auxiliary contacts at DC-13 | | | | | |
| — at 24 V | Α | 10 | | | |
| — at 60 V | Α | 5 | | | |
| — at 110 V | Α | 1.14 | | | |

| Installation/ mounting/ dimensions: | | | | |
|-------------------------------------|----|------------------|--|--|
| Mounting type | | snap-on mounting | | |
| Width | mm | 12 | | |
| Height | mm | 70 | | |
| Depth | mm | 51.5 | | |

| Connections/ Terminals: | | | | |
|---|-------------------------------------|--|--|--|
| Type of electrical connection for auxiliary and control | screw-type terminals | | | |
| current circuit | | | | |
| Type of connectable conductor cross-section | | | | |
| for auxiliary contacts | | | | |
| — finely stranded | | | | |
| — with core end processing | 2x (0.5 1.0 mm²), 2x (0.75 2.5 mm²) | | | |
| for AWG conductors for auxiliary contacts | 2x (18 12) | | | |

| IEC 60947-5-1 | |
|---------------|--|
|---------------|--|

General Product Approval

Functional Safety/Safety of Machinery





Product function positively driven operation acc. to





Yes

Type Examination Type

Type Examination
Certificate

| Test | Chinning | otho |
|--------------|----------|------|
| rest | Shipping | othe |
| Certificates | Approval | |

Special Test Certificate



Declaration of Conformity

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrymall

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TY75611AA00

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

 $\underline{\text{https://support.industry.siemens.com/cs/ww/en/ps/3TY75611AA00}}$

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TY75611AA00&lang=en