

Product type designation



RF160C communication module

RFID COMMUNICATION MODULE RF160C FOR PROFIBUS DP-V0; 2 READERS CAN BE CONNECTED; WITHOUT CONNECTOR BLOCK FOR PROFIBUS

Suitability for operation

PROFIBUS network according to DP-V0 together with RF200/300/600, MOBY D/U

Transmission rate

Transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
Transfer rate / at the point-to-point connection / serial / maximum	115.2 kbit/s

Interfaces

Design of the interface / for point-to-point connection	RS422
Number of readers / connectable	2
Type of electrical connection <ul style="list-style-type: none"> • of the PROFIBUS interface • for supply voltage 	(according to the connection block) (according to the connection block)
Design of the interface / to the reader / for communication	M12, 8-pin

Mechanical data

Material	Thermoplastic (Valox 467, fiberglass reinforced)
Color	IP Basic 714
Tightening torque / of the screw for securing the equipment / maximum	3 N·m

Supply voltage, current consumption, power loss

Supply voltage <ul style="list-style-type: none"> • for DC / Rated value • for DC 	24 V 20 ... 30 V
Consumed current / for DC / at 24 V	

- without connected devices / typical 0.08 A
- with connected devices / maximum 0.8 A

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport 	0 ... 55 °C -40 ... +70 °C -40 ... +70 °C
Protection class IP	IP67
Shock resistance	According to IEC 61131-2
Shock acceleration	300 m/s ²
Resistance against vibration	100 m/s ²

Design, dimensions and weight

Width	60 mm
Height	30 mm
Depth	210 mm
Net weight	0.21 kg
Mounting type	2 x M5 screws
Cable length / for RS 422 interface / maximum	1000 m

Product properties, functions, components / general

Display version	4 LEDs per reader connection, 4 LEDs for device status
<ul style="list-style-type: none"> • Product function / transponder file handler can be addressed 	No
Protocol / is supported	
<ul style="list-style-type: none"> • PROFIBUS DP-V0 protocol • PROFIBUS DP-V1 protocol 	Yes No
Type of parameterization	GSD
Type of programming	FC 44
Type of computer-mediated communication	Cyclic communication

Standards, specifications, approvals

Certificate of suitability	CE, FCC, cULus
MTBF	122 y

Accessories

accessories	Connection block for ECOFAST system or M12, 7/8"
-------------	--

Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center 	http://www.siemens.com/snst http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/automation/net/catalog

- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

09.03.2015