

SERVICE SET FOR MP 277 8" TOUCH, MP 277 8" KEY PROD.
 VERSION "PV15" AND HIGHER MP 277 10" TOUCH PROD.
 VERSION "PV15" AND HIGHER AMOUNT AND CONTENT: SEE
 TECHNICAL DATA



Product type designation

Standards, approvals, certificates

CE mark	Yes
---------	-----

Ambient conditions

Ambient temperature in operation

• Min.	0 °C
• max.	55 °C

Storage/transport temperature

• Min.	-20 °C
• max.	70 °C

Relative humidity

• Operation, max.	95 %
-------------------	------

Scope of supply

Number of sets	1; Content: 14x spring mounting clip, 1x 2-pin female connector
----------------	---

other

Note:	for MP 277 8" Touch, MP 277 8" Key product version "ES 15" and later, MP 277 10" Touch product version "ES 15" and later
-------	--

Usable in the following products

• Product 1	6AV6643-0CB01-1AX0
• Product 2	6AV6643-0CB01-1AX1
• Product 3	6AV6643-0DB01-1AX5
• Product 4	6AV6643-0DB01-1AX1
• Product 5	6AV6643-0CD01-1AX5

- Product 6
- Product 7
- Product 8

[6AV6643-7CD00-0CJ0](#)

[6AV6643-7CD00-0CJ1](#)

[6AV6643-0CD01-1AX1](#)

last modified:

12.03.2015