

HEATER 110-120 V, 10 W;UL-APP. HGK 047-04700.9-00



Figure similar

Model		
product brand name		SIVACON
General technical data		
Operating temperature / minimum	°C	-45
Voltage		
Continuous heat output / at 20 °C	W	10
Inrush current / typical	A	1
Protection class		
Protection class IP		IP44
Main circuit		
Operating voltage		
• Rated value / minimum	V	120
• Rated value / maximum	V	120
• with AC / at 50 Hz / Rated value / minimum	V	100
• with AC / at 50 Hz / Rated value / maximum	V	100
• with AC / at 60 Hz / Rated value / minimum	V	120
• with AC / at 60 Hz / Rated value / maximum	V	120
Operating current / of the slow-blow fuse link	A	1
Product details		
Product component		
• blower		No
• Thermostat		No

Mechanical Design

Height	mm	52
Width	mm	50
Depth	mm	25
Material / of the enclosure		aluminum

Environmental conditions

Relative humidity / Reference value	%	90
Ambient temperature		
• during storage / minimum	°C	-45
• during storage / maximum	°C	70

Certificates

Equipment marking		
• acc. to DIN EN 61346-2		R
• acc. to DIN EN 81346-2		E

General Product Approval

Declaration of Conformity



GOST



UR



UL



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8MR21100C>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8MR21100C/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=8MR21100C

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

11.03.2015