



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE74LS366A Integrated Circuit TTL – Hex Bus Driver with 3–State Outputs

Description:

The NTE74LS366A is a hex bus driver in a 16–Lead plastic DIP type package designed specifically to improve both the performance and density of three–state memory address drivers, clock drivers, and bus oriented receivers and transmitters. The designer has a choice of selected combinations of inverting and non–inverting outputs, symmetrical \overline{G} (active–low control) inputs.

This device features high fan–out, improved fan–in, and can be used to drive terminated lines down to 133 ohms.

Features:

- 3–State Outputs Drive Bus Lines or Buffer Memory Address Registers
- Inverting Outputs

Absolute Maximum Ratings: (Note 1)

Supply Voltage, V_{CC}	7V
DC Input Voltage, V_{IN}	7V
Voltage Applied to Disable 3–State Output	5.5V
Operating Temperature Range, T_A	0°C to +70°C
Storage Temperature Range, T_{stg}	–65°C to +150°C

Note 1. Unless otherwise specified, all voltages are referenced to GND.

Recommended Operating Conditions:

Parameter	Symbol	Min	Typ	Max	Unit
Supply Voltage	V_{CC}	4.75	5.0	5.25	V
High–Level Input Voltage	V_{IH}	2	–	–	V
Low–Level Input Voltage	V_{IL}	–	–	0.8	V
High–Level Output Current	I_{OH}	–	–	–2.6	mA
Low–Level Output Current	I_{OL}	–	–	24	mA
Operating Temperature Range	T_A	0	–	+70	°C

Electrical Characteristics: (Note 2, Note 3)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
Input Clamp Voltage	V_{IK}	$V_{CC} = \text{MIN}, I_I = -18\text{mA}$	-	-	-1.5	V	
High Level Output Voltage	V_{OH}	$V_{CC} = \text{MIN}, V_{IH} = 2\text{V}, V_{IL} = \text{MAX}, I_{OH} = \text{MAX}$	2.4	3.1		V	
Low Level Output Voltage	V_{OL}	$V_{CC} = \text{MIN}, V_{IH} = 2\text{V}, V_{IL} = \text{MAX}$	$I_{OL} = 12\text{mA}$	-	0.25	0.4	V
			$I_{OL} = 24\text{mA}$	-	0.35	0.5	V
Off-State Output Current	I_{OZ}	$V_{CC} = \text{MAX}, V_{IH} = 2\text{V}$	$V_O = 2.4\text{V}$	-	-	20	μA
			$V_O = 0.4\text{V}$	-	-	-20	μA
Input Current	I_I	$V_{CC} = \text{MAX}, V_I = 7\text{V}$	-	-	0.1	mA	
High Level Input Current	I_{IH}	$V_{CC} = \text{MAX}, V_I = 2.7\text{V}$	-	-	20	μA	
Low Level Input Current A Inputs	I_{IL}	$V_{CC} = \text{MAX}, V_I = 0.5\text{V}, \text{Either } \overline{G} \text{ Input at } 2\text{V}$	-	-	-20	μA	
		$V_{CC} = \text{MAX}, V_I = 0.4\text{V}, \text{Both } \overline{G} \text{ Input at } 0.4\text{V}$	-	-	-0.4	mA	
		$V_{CC} = \text{MAX}, V_I = 0.4\text{V}$	-	-	-0.2	mA	
\overline{G} Inputs							
Short-Circuit Output Current	I_{OS}	$V_{CC} = \text{MAX}, \text{Note } 4$	-40	-	-225	mA	
Supply Current	I_{CC}	$V_{CC} = \text{MAX}, \text{Data Outputs} = 0\text{V}, \text{Output Controls} = 4.5\text{V}$	-	12	21	mA	

Note 2. .For conditions shown as MIN or MAX, use the appropriate value specified under “Recommended Operation Conditions”.

Note 3. All typical values are at $V_{CC} = 5\text{V}, T_A = +25^\circ\text{C}$.

Note 4. Not more than one output should be shorted at a time, and duration of the short-circuit should not exceed one second.

Switching Characteristics: ($V_{CC} = 5\text{V}, T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Propagation Delay Time (From Any Input to Y Output)	t_{PLH}	$R_L = 667\Omega, C_L = 45\text{pF}$	-	7	15	ns
	t_{PHL}		-	12	18	ns
Output Enable Time (From Any Input to Y Output)	t_{PZH}		-	18	35	ns
	t_{PZL}		-	28	45	ns
Output Disable Time (From Any Input to Y Output)	t_{PHZ}	$R_L = 667\Omega, C_L = 5\text{pF}$	-	-	32	ns
	t_{PLZ}		-	-	35	ns

Pin Connection Diagram

