## **SIEMENS**

Data sheet 3TC44 13-0BK2

CONTACTOR, SIZE 2, 2-POLE DC 3 AND 5, 32 A AUXILIARY SWITCH 11 (1NO+1NC) 2X AUX. SWITCH SUITABLE FOR ELECTRONICS AC OPERATION 120V 50/60HZ SPECIAL-PURPOSE DEVICE

General technical data:		
Size of contactor		2
Number of poles		2
Equipment marking acc. to DIN 40719 extended		К
according to IEC 204-2 acc. to IEC 750		
Equipment marking acc. to DIN EN 61346-2		Q
Protection class IP		IP00
Ambient temperature during operation	°C	-25 <b>+</b> 55
Control circuit/ Control:		
Type of voltage		AC
Control supply voltage		
• with AC		
— at 50 Hz Rated value	V	120 120
— at 60 Hz Rated value	V	120 120
Main circuit:		
Number of NO contacts for main contacts		2
Number of NC contacts for main contacts		0
Operating current		
● at DC-3 at DC-5		
— at 440 V Rated value	Α	29
— at 220 V Rated value	Α	32
— at 600 V Rated value	Α	21
— at 750 V Rated value	Α	7.5
Operating power		
• at DC-3 at DC-5		
— at 110 V Rated value	kW	2.5
— at 220 V Rated value	kW	5
— at 440 V Rated value	kW	9
— at 600 V Rated value	kW	9
— at 750 V Rated value	kW	4
Auxiliary circuit:		
Number of NO contacts for auxiliary contacts		1
Number of NC contacts for auxiliary contacts		1

Number of CO contacts for auxiliary contacts		2
Connections/ Terminals:		
Type of electrical connection for main current circuit		screw-type terminals
Type of electrical connection for auxiliary and control current circuit		screw-type terminals
Mechanical data:		
Mounting type		screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Mounting type Side-by-side mounting		Yes
Width	mm	81
Height	mm	85
Depth	mm	104

## Certificates/ approvals:

General Product Approval	Functional	Test
	Safety/Safety	Certificates
	of Machinery	









Type Examination
Certificate

Special Test Certificate

Shipping	othe
Approval	



Declaration of Conformity

other

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrymall

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TC44130BK2

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/3TC44130BK2/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/bilddb/index.aspx?attID9=3TC44130BK2&lang=en">http://www.automation.siemens.com/bilddb/index.aspx?attID9=3TC44130BK2&lang=en</a>

