

### Features

- ◆ Shielded metal case with screw terminals
- ◆ Ultra wide 4:1 input voltage ranges  
8.5–36, 16.5–75, 43–160 VDC
- ◆ EN 50155 approval for railway applications
- ◆ Very high efficiency up to 87%
- ◆ Constant current output characteristic for battery load applications
- ◆ Optional with input filter to meet EN55022 class B
- ◆ Overtemperature protection
- ◆ Wide Operating temperature range:  
–40°C to +75°C
- ◆ Reverse input protection
- ◆ Under voltage lock-out
- ◆ I/O isolation 2250 VDC
- ◆ Easy chassis and wall mounting
- ◆ 3-year product warranty



The modules have originally been designed for harsh industrial environment. High EMC immunity against surge, burst, radiated and conducted disturbances and the shock/ vibration and thermal shock resistance make them very popular for stringent requirements. With the extended input voltage ranges that cover the nominal 24, 36, 72 and 110 VDC with  $\pm 40\%$  tolerance and the approval in accordance to EN50155 standard they now also offer a reliable solution for mobile and stationary railway applications. At 100% load the current characteristics goes from constant voltage to constant current what makes the units also suitable for battery charger applications. With protection against over-temperature, overload, short-circuit, reverse input, overvoltage and input under-voltage lock-out they are hard to destroy.

### Models

Order code*	Input voltage	Output voltage	Output current max.	Efficiency typ.
TEP 150-2412WI	9 – 36 VDC (24 VDC nominal)	12 VDC	12.5 A	86 %
TEP 150-2413WI		15 VDC	10 A	86 %
TEP 150-2415WI		24 VDC	6.3 A	87 %
TEP 150-2416WI		28 VDC	5.4 A	87 %
TEP 150-2418WI		48 VDC	3.2 A	86 %
TEP 150-4812WI	18 – 75 VDC (48 VDC nominal)	12 VDC	12.5 A	87 %
TEP 150-4813WI		15 VDC	10 A	87 %
TEP 150-4815WI		24 VDC	6.3 A	88 %
TEP 150-4816WI		28 VDC	5.4 A	88 %
TEP 150-4818WI		48 VDC	3.2 A	87 %
TEP 150-7212WI	43 – 160 VDC (110 VDC nominal)	12 VDC	12.5 A	86 %
TEP 150-7213WI		15 VDC	10 A	86 %
TEP 150-7215WI		24 VDC	6.3 A	87 %
TEP 150-7216WI		28 VDC	5.4 A	87 %
TEP 150-7218WI		48 VDC	3.2 A	86 %

### Options

suffix –F	Modules with input filter to meet EN 55022 class B, see page 5
on demand	Negative (passive = Off) remote On/Off function (standard is passive = On)range

### Input Specifications

Input current (no load)	24 Vin, 12 – 24 VDC models: 80 mA typ. 24 Vin, 28 – 48 VDC models: 130 mA typ. 48 Vin, 12 – 24 VDC models: 60 mA typ. 48 Vin, 28 – 48 VDC models: 70 mA typ. 110 Vin, 12 – 24 VDC models: 30 mA typ. 110 Vin, 28 – 48 VDC models: 40 mA typ.
Start-up voltage / under voltage lock-out	24 Vin models: 9 VDC / 8.2 VDC typ. 48 Vin models: 18 VDC / 16.2 VDC typ. 110 Vin models: 43 VDC / 34.5 VDC typ.
Surge voltage (1sec. max.)	24 Vin models: 50 V 48 Vin models: 100 V 110 Vin models: 170 V
Conducted noise (input)	EN 55022 class A, FCC part 15, class A without external components. optional filter for class B – suffix F
EMC immunity	EN 50121-3-2 EN 61000-4-2, air ±8 kV, contact ±6 kV, perf. criteria A EN 61000-4-3, 10 V/m, perf. criteria A EN 61000-4-4, ±2 kV, perf. criteria A EN 61000-4-5, ±1 kV perf. criteria A – ESD (electrostatic discharge) – Radiated immunity – Fast transient / surge (with input capacitor for models without filter module) – Input capacitor: 24 Vin models: Nippon chemi-con KY 470 µF, 50 V, ESR 45 mOhm 48 Vin models: Nippon chemi-con KY 220 µF, 100 V, ESR 48 mOhm 110 Vin models: Nippon chemi-con KXJ series, 150 µF, 200V models with filter module (suffix F): no input capacitor required – Conducted immunity EN 61000-4-6, 10 Vrms, perf. criteria A
Reverse voltage protection	parallel diode (input fuse required)
Recommended input fuse (slow blow)	24 Vin models: 15 A 48 Vin models: 10 A 110 Vin models: 5 A

### Output Specifications

Voltage set accuracy	±1 %
Output voltage adjustment	+20 % by external resistor (see application note)
Regulation	– Input variation Vin min. to Vin max. 0.2 % max. – Load variation 0 – 100 % 0.4 % max.
Temperature coefficient	±0.02 %/K
Minimum load	not required
Ripple and noise (20 MHz Bandwidth)	12 & 15 VDC models: 100 mVpk-pk max. 24 & 28 VDC models: 200 mVpk-pk max. 48 VDC models: 350 mVpk-pk max.
Start up time (nominal Vin and constant resistive load)	25 ms typ. (at power On or remote On)
Transient response (25 % load step change)	200 µs typ.
Output current	– Constant voltage (CV) up to 110 % of Iout max. – Constant current (CC) above 110 % of Iout max.
Over voltage protection	at 125 –140 % of Vout nom.
Short circuit protection	indefinite, automatic recovery
Capacitive load	12 VDC models: 40'000 µF max. 15 VDC models: 26'000 µF max. 24 VDC models: 10'000 µF max. 28 VDC models: 7'600 µF max. 48 VDC models: 2'600 µF max.

## General Specifications


Temperature ranges	<ul style="list-style-type: none"> <li>- Operating</li> <li>- Case temperature</li> <li>- Storage</li> </ul>	-40°C to +75°C +100°C max. -55°C to +125°C
Thermal consideration	<ul style="list-style-type: none"> <li>- Mounting surface</li> <li>- Derating and temperature test point</li> </ul>	Optimize thermal coupling to heat conducting surface. Not to mount on flammable surface! see application note
Over temperature protection		at 110°C (auto restart)
Vibration and thermal shock		acc. MIL-STD-810F
Humidity (non condensing)		95 % rel H max.
Reliability, calculated MTBF (MIL-HDBK-217F, at +70°C, ground benign)		>495'000 h
Isolation voltage (60 sec.)	<ul style="list-style-type: none"> <li>- Input/Output</li> <li>- Input/Case</li> <li>- Output/Case</li> </ul>	2250 VDC (functional insulation) 1500 VDC 1500 VDC
Isolation capacitance	- Input/Output	3500 pF max.
Isolation resistance	- Input/Output (500 VDC)	>1 GOhm min.
Switching frequency		220 – 330 kHz depending on model (puls width modulation)
Safety standards		UL 60950-1, IEC/EN 60950-1
Safety approvals	<ul style="list-style-type: none"> <li>- UL/cUL 60950-1</li> <li>- CB test certificate (IEC 60950-1)</li> <li>- Railway</li> </ul>	<a href="http://www.ul.com">www.ul.com</a> -> certifications -> File e188913 <a href="http://www.tracopower.com/products/tep150wi-cb.pdf">www.tracopower.com/products/tep150wi-cb.pdf</a> (72 Vin models pending) <a href="http://www.tracopower.com/products/tep150wi-coc.pdf">www.tracopower.com/products/tep150wi-coc.pdf</a>
Remote On/Off	<ul style="list-style-type: none"> <li>- positive logic (standard)</li> <li>- negative logic (option -N)</li> <li>- Off idle current:</li> </ul>	<ul style="list-style-type: none"> <li>- On: 3 to 12 VDC or open circuit</li> <li>- Off: 0 to 1.2 VDC or short circuit pin 5 and 3</li> <li>- On: 0 to 1.2 VDC or short circuit pin 5 and 3</li> <li>- Off: 3 to 12 VDC or open circuit</li> <li>3 mA</li> </ul>
Environmental compliance	<ul style="list-style-type: none"> <li>- Reach</li> <li>- RoHS</li> </ul>	<a href="http://www.tracopower.com/products/reach-declaration.pdf">www.tracopower.com/products/reach-declaration.pdf</a> RoHS directive 2011/65/EU

## Physical Specifications

Casing material	metal
Potting material	silicone (UL 94V-0 rated)
Case protection	IP 50 (in accordance to IEC/EN60529)
Weight	300 g (10.6oz)

**Application note:** [www.tracopower.com/products/tep150wi-application.pdf](http://www.tracopower.com/products/tep150wi-application.pdf) (110 Vin models pending)

**Outline Dimensions**




Pin Connection		
pin	function	recommended wire
1	+ Vin	14 - 16 AWG
2	+ Vin	14 - 16 AWG
3	- Vin	14 - 16 AWG
4	- Vin	14 - 16 AWG
5	Remote On/Off	14 - 24 AWG
6	+ Vout	14 - 16 AWG
7	- Vout	14 - 16 AWG
8	Trim	14 - 24 AWG
9	Trim	14 - 24 AWG

Weight: 300 g (10.6oz)

Dimensions in [mm], ( ) = Inch  
Mounting slot tolerance:  $\pm 0.25$  ( $\pm 0.001$ )  
Case tolerances:  $\pm 0.5$  ( $\pm 0.02$ )

**Outline Dimensions**



Pin Connection		
pin	function	recommended wire
1	+ Vin	14 - 16 AWG
2	+ Vin	14 - 16 AWG
3	- Vin	14 - 16 AWG
4	- Vin	14 - 16 AWG
5	Remote On/Off	14 - 24 AWG
6	+ Vout	14 - 16 AWG
7	- Vout	14 - 16 AWG
8	Trim	14 - 24 AWG
9	Trim	14 - 24 AWG

Weight: 435 g (15.3oz)

Dimensions in [mm], ( ) = Inch  
Mounting slot tolerance:  $\pm 0.25$  ( $\pm 0.001$ )  
Case tolerances:  $\pm 0.5$  ( $\pm 0.02$ )

Specifications can be changed without notice! Make sure you are using the latest documentation, downloadable at [www.tracopower.com](http://www.tracopower.com)