

## 300 Hex torque-indicator, Hex-Plus, 2.0 mm, 1.4 Nm

### Series Torque-indicators



**EAN/GTIN:** 4013288096425  
**Part no.:** 05027910001  
**Article no.:** 300 Hex

**Dimension:** 170x37x37 mm  
**Weight:** 124 g  
**Country of origin:** CZ  
**Customs tariff number:** 82054000

- Torque -indicator with pre-set and tamperproof torque value
- Distinct audible and perceivable excess load signal when the pre-set torque value is reached
- Non-adjustable and tamperproof
- Unlimited torque for loosening seized screws
- Multi-component Kraftform handle for fast and ergonomic screwdriving

Wera torque screwdriver with fixed torque for hexagon socket screws. Tamperproof and with a slim hex blade. Unlimited torque for loosening seized screws. Multi-component Kraftform handle for pleasant, ergonomic working that prevents blisters and calluses. Hard gripping zones for high working speeds whereas soft zones ensure high torque transfer. Comes with Hex-Plus profile which avoids any rounding of the screw head. The Black Point tip offers high corrosion protection and an exact fit.

#### Weblink

[http://products.wera.de/en/torque\\_tools\\_series\\_torque-indicators\\_300\\_hex.html](http://products.wera.de/en/torque_tools_series_torque-indicators_300_hex.html)

Wera - 300 Hex  
05027910001 - 4013288096425

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

Torque-indicators




Wera torque-indicators have been factory pre-set to values recommended by leading carbide tool manufacturers. These tightening values relate specifically to the size of the TORX®, TORX PLUS® or hexagon socket screw. Torque indicators ensure safe and easy loosening of screw connections. Precision : ± 10 %

Torque-indicators




Suitable for applications requiring a non-adjustable i.e. a tamperproof torque blade assembly.

Torque-indicators



Some screw connections require specific torque values so that they can be tightened or loosened easily. Wera torque-indicators are pre-set to torque values recommended by leading carbide tool manufacturers. Pre-set torque between 0.6 Nm and 5.0 Nm, for TORX®, TORX PLUS® and hexagon socket screws, unlimited loosening torque, two handles, tamper-proof.

Precisely adjusted



Torque blade assembly precisely adjusted to the respective screw size for the TORX®, TORX PLUS® and hexagon socket screw profiles.

For difficult-to-access places




Slim 4 mm hexagon blades to reach screws in difficult-to-access places.

Tamperproof



Non-adjustable and tamperproof.

Excess-load signal



Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

Weblink

[http://products.wera.de/en/torque\\_tools\\_series\\_torque-indicators\\_300\\_hex.html](http://products.wera.de/en/torque_tools_series_torque-indicators_300_hex.html)

Wera - 300 Hex  
05027910001 - 4013288096425

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: info@wera.de

More variants of this product family:



nm

ft. lb.

mm

mm

mm

mm

inch

|                    |            | nm         | ft. lb.    | mm       | mm         | mm        | mm         | inch          |
|--------------------|------------|------------|------------|----------|------------|-----------|------------|---------------|
| <b>05027910001</b> | <b>2.0</b> | <b>1.4</b> | <b>1.0</b> | <b>4</b> | <b>3.5</b> | <b>65</b> | <b>105</b> | <b>2 9/16</b> |
| 05027911001        | 2.5        | 2.0        | 1.5        | 4        | 3.8        | 65        | 105        | 2 9/16        |
| 05027912001        | 3.0        | 3.0        | 2.2        | 4        | 3.8        | 65        | 105        | 2 9/16        |

**Weblink**

[http://products.wera.de/en/torque\\_tools\\_series\\_torque-indicators\\_300\\_hex.html](http://products.wera.de/en/torque_tools_series_torque-indicators_300_hex.html)

Wera - 300 Hex

05027910001 - 4013288096425

Wera Werkzeuge GmbH

Korzter Straße 21-25

D-42349 Wuppertal

Tel: +49 (0)2 02 / 40 45-0

E-Mail: [info@wera.de](mailto:info@wera.de)