



TOUCH PEN, THICK, FOR RESISTIVE TOUCHSCREEN, OPTIMIZED FOR USE WHEN WEARING GLOVES, INCLUDING SCREW-ON WALL BRACKET AMOUNT AND CONTENT: SEE TECHNICAL DATA

Product type designation	
Installation type/mounting	
Wall mounting/direct mounting possible	Yes; Terminal holder can be attached
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature in operation	
• Min.	0 °C
• max.	55 °C
Storage/transport temperature	
• Min.	-20 °C
• max.	70 °C
Relative humidity	
• Operation, max.	90 %
Mechanics/material	
Screw type	
• Torx	Yes
Material of housing	
• plastic	Yes
Dimensions	
Height	155 mm; Length
Thickness	20 mm; Diameter

Scope of supply	
Delivery unit in items	1; Optional for extension units of the PRO devices
other	
Note:	for resistive touch screens, optimized for operating while wearing gloves
Usable in the following products	
• Product 1	6AV6642-0AA11-0AX0
• Product 2	6AV6642-0AA11-0AX1
• Product 3	6AV6642-0BD01-3AX0
• Product 4	6AV6642-0BA01-1AX1
• Product 5	6AV6642-0BC01-1AX1
• Product 6	6AV6642-0DC01-1AX0
• Product 7	6AV6642-0DA01-1AX0
• Product 8	6AV6545-0DA10-0AX0
• Product 9	6AV6545-0DB10-0AX0
• Product 10	6AV6545-0AA15-2AX0
• Product 11	6AV3637-1PL00-0AX0
• Product 12	6AV6642-0EA01-3AX0
• Product 13	6AV6644-0CB01-2AX0
• Product 14	6AV6643-8AD10-0AA0
• Product 15	6AV6640-0CA01-0AX0
• Product 16	6AV6545-0AH10-0AX0
• Product 17	6AV6545-0AH10-0AX1
• Product 18	6AV6640-0CA01-0AX0
• Product 19	6AV6545-0CC10-0AX0
• Product 20	6AV2123-2*
last modified:	12.03.2015