

Powerswitch for EM systems for SON

HID-Regulator BSD 250/400 L40 230V 50Hz HD1-118

Power-switches with internal timer for HID PS 400 T5 / HID PS R 400 T5

Product data

• General Characteristics

Rated Number of Lamps	1 piece
Rated Ballast-Lamp Power	250/400
Rated Lamptype	SON
Application code	L40
Line Voltage	230 V
Line Frequency	50 Hz
Design	HD1-118

• Operating Characteristics

Input current with PF-correct.	0.90 A
Input current w/o PF-correct.	2.70 A
Mains voltage safety (AC)	-10%/+10%
Mains voltage performance (AC)	-8%/+6%
Power losses gear	6.8 W

• Wiring Characteristics

Connector type	Screw
Striplength	7.0 mm
Wcs Ballast contacts	0.70-6.00 mm2

• Temperature Characteristics

T-storage	-30 (min), 130 (max) C
T-winding maximum (tw)	130 (max) C
Delta-T normal conditions	35 C

• Approval & Application Chars

CE marking	Yes
ENEC certificate	No



• Product Dimensions

Length A1	118.0 mm
Fixing Hole Distance	103.0 mm
Length A2	
Width B1	65.0 mm
Height C1	53.0 mm
Fixing Hole Diameter D1	6.2 mm

• Product Data

Order code	913625130326
Full product code	913625130326
Full product name	BSD 250/400 SON L40 230V 50Hz HD1-118
Order product name	BSD 250/400 SON L40 230V 50Hz HD1-118
Pieces per pack	1
Packing configuration	6
Packs per outerbox	6
Bar code on pack - EAN1	8711500916389
Bar code on outerbox - EAN3	8711500061799
Logistic code(s) - 12NC	913625130326
Net weight per piece	1.300 kg

Dimensional drawing



Product	A1 (Norm)	A2 (Norm)	B1 (Norm)	C1 (Norm)	D1 (Norm)
BSD 250/400 L40 230V 50Hz	118.0	103.0	65.0	53.0	6.2
HD1-118					



© 2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2011, June 7
data subject to change