



SIMATIC S7-300 STABILIZED POWER SUPPLY PS307 INPUT:
120/230 V AC OUTPUT: DC 24 V DC/10 A

Technical specifications

Product	PS 307
Power supply, type	24 V/10 A

Input

Input	1-phase AC
Supply voltage 1 with AC Rated value	120 V
Supply voltage 2 with AC Rated value	230 V
• Note	Automatic range selection
Input voltage 1 with AC	85 ... 132 V
Input voltage 2 with AC	170 ... 264 V
Wide-range input	No
Overvoltage resistance	$2.3 \times V_{in}$ rated, 1.3 ms
Mains buffering at I _{out} rated, min.	20 ms; at $V_{in} = 93/187$ V
Rated line frequency	50 ... 60 Hz
Rated line range	47 ... 63 Hz
Input current at rated input voltage 120 V Rated value	4.2 A
Input current at rated input voltage 230 V Rated value	1.9 A
Switch-on current limiting (+25 °C), max.	55 A
Duration of inrush current limiting at 25 °C maximum	3 ms
I ² t, max.	3.3 A ² ·s
Built-in incoming fuse	T 6.3 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 10 A characteristic C

Output	
Output	Controlled, isolated DC voltage
Rated voltage Vout DC	24 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.5 %
Residual ripple peak-peak, max.	50 mV
Residual ripple peak-peak, typ.	15 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	150 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	60 mV
Product function Output voltage adjustable	No
Output voltage setting	-
Status display	Green LED for 24 V OK
On/off behavior	No overshoot of Vout (soft start)
Startup delay, max.	2 s
Voltage rise, typ.	10 ms
Rated current value Iout rated	10 A
Current range	0 ... 10 A
Active power supplied typical	240 W
Short-term overload current on short-circuiting during the start-up typical	38 A
Duration of overloading capability for excess current on short-circuiting during the start-up	80 ms
Short-term overload current at short-circuit during operation typical	38 A
Duration of overloading capability for excess current at short-circuit during operation	80 ms
Parallel switching for enhanced performance	Yes

Efficiency	
Efficiency at Vout rated, Iout rated, approx.	90 %
Power loss at Vout rated, Iout rated, approx.	27 W

Closed-loop control	
Dynamic mains compensation (Vin rated ±15 %), max.	0.1 %
Dynamic load smoothing (Iout: 50/100/50 %), Uout ± typ.	2 %
Setting time maximum	0.1 ms

Protection and monitoring	
Output overvoltage protection	Additional control loop, shutdown at < 28.8 V, automatic restart
Current limitation	11 ... 12 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
Enduring short circuit current RMS value maximum	12 A

Overload/short-circuit indicator	-
----------------------------------	---

Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current maximum	3.5 mA
Leakage current typical	0.6 mA
CE mark	Yes
UL/CSA approval	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 142), File E143289
Explosion protection	ATEX (EX) II 3G Ex nA II T4; cULus (ISA 12.12.01, CSA C22.2 No.213) Class I, Div. 2, Group ABCD, T4, File E330455
Certificate of suitability IECEx	No
Certificate of suitability NEC Class 2	No
FM approval	Class I, Div. 2, Group ABCD, T4
CB approval	No
Marine approval	In S7-300 system
Degree of protection (EN 60529)	IP20

EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

Operating data

Ambient temperature during operation	0 ... 60 °C
• Note	with natural convection
Ambient temperature during transport	-40 ... +85 °C
Ambient temperature during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

Mechanics

Connection technology	screw-type terminals
Connections Supply input	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded
Connections Output	L+, M: 4 screw terminals each for 0.5 ... 2.5 mm ²
Connections Auxiliary	-
Width of the enclosure	80 mm
Height of the enclosure	125 mm
Depth of the enclosure	120 mm
Weight, approx.	0.8 kg
Product property of the enclosure housing for side-by-side mounting	Yes
Installation	Can be mounted onto S7 rail

Mechanical accessories

Mounting adapter for standard mounting rail (6EP1971-1BA00)

Other information

Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)