

# USB Cable 2.0 Male Type A to B

**multicomp** PRO


**RoHS  
Compliant**



## Specifications

Connector to Connector	: Type A Plug to Type B Plug
USB Standard	: USB 2.0
Temperature Range	: -15°C to +80°C
Cable Length	: 1m (3.28ft)
Jacket Colour	: Black

## Diagram



**Pin Out : 5.**

### Note:

- Cable Spec: 30AWG (7/0.10Cu)×1P+26AWG(7/0.15Cu)×2C+AD(1/0.254Cu)B(48/0.12ALMG)  
 Jacket Material : PVC OD: 4.5±0.2mm  
 Colour : Black  
 Cable Printing : USB 2.0 Cable fully rated 80°C 30V
- Connector A : USB A Male Solder Type  
 Insulation : White  
 Contact : Gold Plated  
 Shell : Fe (SPCC) Nickel Plated
- Connector B : USB B Male Solder Type  
 Insulation : White  
 Contact : Gold Plated  
 Shell : Fe (SPCC) Nickel Plated
- Over Mold : PVC-Black
- Parameter Settings : CT-8681FA
  - Conductive Resistance : 5Ω
  - Insulative Resistance : 5MΩ (Min.)
  - Hi-Pot : DC 300V/10ms, 1.5mmA/I, 50Hz, 0.03s

## Part Number Table

Description	Part Number
USB Cable, 2.0 Male Type A to B, Black, 1m	MP009288

Dimensions : Millimetres

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro  
 Farnell.com/multicomp-pro  
 sg.element14.com/b/multicomp-pro

**multicomp** PRO