

**SAI Active
SAI-AU M8 SB 8DI**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Digital M8 extension modules for the Universal-Pro system

General ordering data

Type	SAI-AU M8 SB 8DI
Order No.	193860000
Version	SAI Active, Subbus, Complete modul
GTIN (EAN)	4032248612611
Qty.	1 pc(s).

SAI Active SAI-AU M8 SB 8DI

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

Dimensions and weights

Length	155 mm	Width	30 mm
Height	32 mm	Net weight	271 g

Configuration

System integration	automatic
--------------------	-----------

Connections

Connection to Subbus (SUB-IN)	1 x M8 plug 4-pole, A-coded	Connection to Subbus (SUB-OUT)	1 x M8 female 4-pole, A-coded
I/O connections	8 x M8 socket 3-pole		

Digital inputs

Input current, high	2 mA to 15 mA in accordance with EN 61131-2 Type 1	Input current, low	< 15 mA in accordance with EN 61131-2 Type 1
Input filter	1 ms, 3 ms, 5 ms, 10 ms, configurable	Input voltage, high	>15 V in accordance with EN 61131-2 Type 1
Input voltage, low	<5 V in accordance with EN 61131-2 Type 1	Permitted input voltage	-30 V to +30 V (protected against polarity reversal)
Separation of potentials to module electronics [digital inputs]	none		

General data

Certificate	CE, cULus	Earth	< 200 g
Housing main material	Pocan, PBT	L x W x H	155 / 30 / 32
Protection degree	IP 67	UL 94 flammability rating	5VA

Fieldbus

Addressing	automatic	Bus system	Subbus
------------	-----------	------------	--------

Functional inputs

Input filter	1 ms, 3 ms, 5 ms, 10 ms, configurable
--------------	---------------------------------------

Supply voltage

Limits	18 V DC ... 30 V DC	Operating voltage	24 V
Reverse polarity protection	Yes		

Classifications

ETIM 3.0	EC001597	UNSPSC	43-17-27-10
eClass 5.1	27-25-04-03	eClass 6.2	27-24-26-04
eClass 7.1	27-24-26-04		

Datenblatt

SAI Active
SAI-AU M8 SB 8DI

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technische Daten

Approvals

Approvals

