



Part Number: 70008PU

DataTuff® PROFINET Cat 5e Type C - Continuous Flexing Cable, Trailing AWM 20549

[Request Sample](#)

Product Description

PROFINET Category 5e, 2 Pair (Quad), AWG 22 (19), Trailing, Overall Foil+ 85% Braid, PUR No Halogen Outer Jacket

Technical Specifications

Product Overview

Environmental Space:	Indoor
----------------------	--------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Construction n x D	No. of Conductors
22	Stranded	TC - Tinned Copper	19x0.15 mm	4

Conductor Count:	4
Total Number of Pairs:	2
Conductor Size:	22 AWG

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance
PO - Polyolefin	1.63 mm	0.05 mm

Color Chart

Number	Color
Quad 1	White & Blue & Yellow & Orange

Inner Jacket Material

Material	Nominal Diameter
FRNC / LSZH Bedding	4.3 mm

Outer Shield Material

Type	Material	Min. Coverage [%]
Tape	Aluminum/Polyester	
Braid	TC - Tinned Copper	85 %

Outer Jacket Material

Material	Color	Nominal Diameter	Diameter +/- Tolerance	Separator Material
PUR (Halogenfree)	Green (RAL 6018)	6.5 mm	0.2 mm	Non-woven foil

Construction and Dimensions

Cabling

Description
1 quad with center filler

Electrical Characteristics

Conductor DCR

Max. Conductor DCR
57.1 Ohm/km

Shielding:	Foil + Braid(s)
------------	-----------------

Impedance

Frequency [MHz]	Nominal Characteristic Impedance	Nominal Characteristic Tolerance
1 - 100	100 Ohm	15 Ohm

Delay

Max. Delay	Nominal Velocity of Propagation (VP) [%]
530 ns/100m	68 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. ACRF (ELFEXT) [dB]	Min. SRL (Structural Return Loss)
1 MHz	2.1 dB/100m	65 dB	64 dB	
4 MHz	4 dB/100m	56 dB	52 dB	23 dB
10 MHz	6.3 dB/100m	50 dB	44 dB	25 dB
16 MHz	8 dB/100m	47 dB	40 dB	25 dB
31.25 MHz	11.4 dB/100m	43 dB	34 dB	23.6 dB
62.5 MHz	16.5 dB/100m	38 dB	28 dB	21.5 dB
100 MHz	21.3 dB/100m	35 dB	24 dB	20.1 dB

Transfer Impedance

Frequency [MHz]	Transfer Impedance
10 Mhz	Max. 10 mOhm/m

Voltage

UL Voltage Rating	Voltage Rating [V]
300 V	300 V

Temperature Range

Installation Temp Range:	-5°C To +60°C
UL Temp Rating:	80°C
Storage Temp Range:	-40°C To +80°C
Operating Temp Range:	-40°C To +80°C
Operating Temp Range (Drag Chain Op):	-5°C To +60°C

Mechanical Characteristics

Oil Resistance:	IEC 60811-2-1
Torsion Test: Min Number of Torsions:	1000000
Torsion Test: Description:	+/- 180° ,12x/min over 1mtr
Min No. of Drag Chain Cycles:	5000000
Drag Chain Parameters:	a= 3m/s ² v= 3 m/s and r= 60 mm

Standards

UL AWM Style:	UL AWM 20549
ISO/IEC Compliance:	ISO/IEC 11801 Ed. 2.2:2002/A2:2010/C1:2011
Data Category:	Category 5e

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
---------------------------------------	------------

Flammability, LS0H, Toxicity Testing

CSA Flammability:	FT2
-------------------	-----

Part Number

Variants

Item #	Color
70008PU.011000	Green
70008PU.01305	Green
70008PU.01500	Green
70008PU.01B100	Green

Patent:	https://www.belden.com/resources/patents
---------	---

History

Revision Number:	5
------------------	---

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.