

## TECHNICAL DATA SHEET



**ALEX S2** 

No. 16520

Sz. 36-48

LABELLING ACCORDING TO STANDARD		
In accordance with EN ISO 20345 S2 SRC		
Form B	Safety boot, mid cut	
SRC SLIP RESISTANCE	SLIP RESISTANCE: When it comes to slip resistance as defined by EN ISO 20345, SRC signifies the best possible rating a safety shoe can reach.	
FIT	AREAS OF APPLICATION	
	<ul> <li>Indoors and outdoors</li> <li>Industry, storage, transport, construction etc.</li> <li>Areas where exposure to moisture is expected (S2)</li> </ul>	
FEATURES		
Design	Modern and sporty design	
Full, padded bellows tongue	<ul><li>Extremely comfortable</li><li>Prevents pressure points</li><li>Prevents penetration of dirt</li></ul>	
Collar padding	<ul> <li>Extremely comfortable</li> <li>Ankle-wrapping upper edging, softly padded, for good stability and firm support in the shoe (form B)</li> </ul>	
Reflective material	Good visibility in the dark	
Sizes (unisex model)	<ul><li>Expanded size range</li><li>Available in sizes 36-48</li></ul>	



FEATURES			
PU toe protection (polyurethane)	<ul> <li>Directly applied toe protection</li> <li>Excellent wear protection in the toe area</li> <li>Protects the upper leather in this area against premature wear</li> </ul>		
UPPER MATERIAL			
Cowhide leather	<ul> <li>Areas of application S2/S3</li> <li>Natural material</li> <li>Wear-resistant</li> <li>Breathable</li> <li>Water penetration/absorption in accordance with EN ISO 20345 S2</li> </ul>		
Textile material Cordura® (hydrophobized)  CORDURA®	<ul> <li>Areas of application S2/S3</li> <li>Synthetic material</li> <li>Particularly resistant to wear and tear</li> <li>Retains its shape</li> <li>Tear-resistant</li> <li>Water penetration/absorption in accordance with EN ISO 20345 S2</li> <li>Quick drying</li> <li>Abrasion resistant and light</li> <li>By hydrophobation, higher resistance against water penetration and water absorption</li> </ul>		
LINING			
Climate-regulating textile lining	<ul> <li>Climate-regulating</li> <li>Good ventilation</li> <li>Skin-friendly</li> <li>High absorption and emission of moisture</li> </ul>		
Heel pocket lining	<ul><li>Abrasion-resistant microfibre material, sturdy</li><li>Comfortable</li></ul>		
TOE PROTECTION CAP			
Steel toe cap	<ul> <li>Protection against impacts of min. 200 joules and pressure loading of min. 15 kN</li> <li>Permanent edge coverage for cushioning</li> <li>Ergonomically shaped</li> <li>Comfortable toe-room</li> <li>Good coverage of the little toe area</li> </ul>		
INLAY SOLE			
Full-length inlay sole	<ul> <li>Excellent moisture absorption and release providing a comfortable foot climate</li> <li>Exchangeable</li> <li>Sturdy</li> <li>Antistatic</li> </ul>		



INSOLE		
Antistatic soft-	fleece insole	<ul> <li>Antistatic, even when 100% dry and without the need for additional aids to provide a bridge to the outsole</li> <li>Approx. 50% lighter than comparable soles made of natural materials</li> <li>Flexible and shape-retaining</li> <li>Good air permeability</li> <li>Excellent wear resistance</li> <li>High moisture absorption</li> <li>Quick drying (virtually overnight)</li> </ul>
OUTSOLE		
	Double-density sole with profile NEW BASIC	<ul><li>Antistatic</li><li>Excellent slip resistance</li></ul>
	Outsole: PU	<ul> <li>Colour: grey</li> <li>Particularly abrasion-resistant</li> <li>Heat-resistant to approx. 130°C, flexible at cold temperatures to approx20°C</li> <li>Oil and fuel resistant</li> </ul>
	Midsole: PU	<ul> <li>Colour: black</li> <li>The soft PU core provides a good impact absorption and high comfort</li> </ul>