



Figure similar

INSERTABLE JUMPER, 3-POLE, FULLY INSULATED, INSERTED IN LOCKING SLEEVE AND LATCHED FOR 95 MM² TERMINALS

Main circuit

Operating current / Rated value	A	232
---------------------------------	---	-----

Mechanical Design

Mounting type		others
Contact spacing	mm	95

Certificates

Design tested acc. to type of protection / EEx e		No
--	--	----

General Product Approval	Declaration of Conformity
--------------------------	---------------------------



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH90203BA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH90203BA00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH90203BA00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

11.03.2015