



(SET BLACK & RED) PROBE TO RIGHT ANGLE

For data sheets / specifications of the kit individual components, visit the Pomona web site at:
www.pomonaelectronics.com

FEATURES:

- Fits Fluke, H-P, Tektronix and Wavetek meters configured with non-sheathed standard and 4 mm banana jacks.
- Test probe body & banana plug body are molded directly to 48" (122 cm) high strand count/high temperature silicone leads for added pull strength and flexibility.
- Medium alligators are insulated for added safety and can quickly attach to the 0.080" (2.03 mm) O.D. probe tip.
- Medium alligators have an overall length of 2.25" (5.7 cm) and grip up to 0.30" (7.62 mm) O.D. terminals.
- Slide-on extended tips have an overall length of 4" (10.16 cm) & attaches to the probe tip to allow access to hard to reach test points.
- Slide-on Extended Tip is insulated to the point to prevent accidental shorting.

Kit Accessories:

Model 5672A Test Probes: Test Probes, set of one black and one red

Model 5682: Slide-on Extended Tip, set of one black and one red (Replacement P/N: 5682-0/-2)

Model 5916A: Medium Alligators, set of one black and one red (Replacement P/N: 5916A).

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Sales: 800-490-2361 Fax: 888-403-3360 Technical Assistance: technicalsupport@pomonatest.com
For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com

MATERIALS:

Model: **5672A Test Probes:** Over molded Probe Test Lead w/ right angle banana plugs:

Probe body and banana plug body: Polypropylene – Fire Retardant, Tip: Stainless Steel Wire: 18 AWG, 65 x 36 Tinned Copper Strand, Silicone Insulation, O.D. 0.144” (3.7 mm). Length: 48” (122 cm), Banana Plug:

Insulation: Polypropylene – Fire Retardant, Plug Body: Brass Nickel Plated, Spring: Beryllium Copper, Nickel Plated, **RATINGS:** Operating Voltage: 1,000 VAC/DC, Current: 10 Amps.

Model: **5682:** Probe Extended Tip Adapter:

Insulation: Polypropylene, Fire Retardant, Color: one black and one red

Probe Tip: Stainless Steel with Kynar Insulation Sleeve to Tip End

RATINGS: +80°C (+176°F) Max

Model: **5916A:** Medium Alligator:

Insulation: Polypropylene, Fire Retardant, UL94 V-2 Rated, Color: one black and one red

Body: Steel, Nickel Plated, Spring: Music Wire

RATINGS: 300 VRMS, Current: 5 Amps

All dimensions are in inches. Tolerances (except noted): .xx = ±.02” (.51 mm), .xxx = ±.005” (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA