


SD20-H15-5.5







Application

Fastening of metal decks, liner trays onto metal beams

Componen	t 1 (t _i)	Compone	$\Sigma_{max} \mathbf{t_{I}} + \mathbf{t_{II}}$	
Steel	0.50-2.0	Steel	4.0-18.0	20.0
Steel	2×0.50-1.50			21.0
Aluminium	0.50-2.0			20.0

Fastener material

Carbon steel, Durocoat® 480

Approvals

CE₁₉ ETA-10/0198

Features and Benefits

- Self drilling fastener suitable for installation of metal decks and liner trays
- High shear resistance achieved by optimized fastener geometry
- High corrosion durability thanks to special galvanic zinc coating

Documentation

Approval document (ETA) I Declaration of performance (DoP)







Fastener in carbon steel onto steel

Product code	PU	L	CL _{met}	t _{fix, met}	
SD20-H15-5,5×50	500	50	0–24	0-6/20	1673850

 $\overline{t_{\text{fix, met.}} \text{ CL}_{\text{met, min.}} - (\text{CL}_{\text{met, max.}} - t_{\text{II, max.}} \text{ or load-bearing clamping length according ETA})} / (\text{CL}_{\text{met, max.}} - t_{\text{II, min.}})$



Accessories/Ancillaries

Product code	PU	Drive	Head drive	
E308-¼"-50	1	1/4"	HEX8	1646160