# PRODUCT DATASHEET CP17412\_YASMEEN-70-M-C

#### YASMEEN-70-M-C

~26° wide beam. Assembly with holder C compatible with LEDiL HEKLA. Black version.

#### SPECIFICATION:

**Dimensions** Ø 69.9 mm 39.9 mm Height yes 🕕 **ROHS** compliant



#### **MATERIALS:**

Colour Component **Type** Material **Finish** YASMEEN-70-M Single lens **PMMA** clear YASMEEN-70-HLD-C Holder C PC black


#### **ORDERING INFORMATION:**

» Box size: 476 x 273 x 305 mm

Component Qty in box MOQ MPQ Box weight (kg) CP17412\_YASMEEN-70-M-C Single lens 105 105 15 10.0




# **PRODUCT** CP17412\_YASMEEN-70-M-C




See also our general installation guide: www.ledil.com/installation\_guide














LED Vesta DTW 9mm (4W/6W/12W)


FWHM / FWTM 27.0° / 43.0°
Efficiency 83 %
Peak intensity 3.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
Bender Wirth: 652b Hekla



# **CITIZEN**

LED CLL02x/CLU02x (LES10)

FWHM / FWTM 25.0° / 42.0°
Efficiency 83 %
Peak intensity 3.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17435\_HEKLA-G2-C



# **CITIZEN**

LED CLL03x/CLU03x
FWHM / FWTM 25.0° / 45.0°


Efficiency 82 %

Peak intensity 3.7 cd/lm

LEDs/each optic 1

Light colour White

Required components: F17438\_HEKLA-G2-I




#### CREE - LED

LED CMA1516 FWHM / FWTM 26.0° / 42.0°


Efficiency 83 %
Peak intensity 3.9 cd/lm
LEDs/each optic 1
Light colour White

F17436\_HEKLA-G2-D

Required components:








Published: 21/10/2020








#### **PHILIPS**

LED Fortimo SLM L09 CoB

FWHM / FWTM 25.0° / 42.0°
Efficiency 82 %
Peak intensity 3.9 cd/lm
LEDs/each optic 1

Light colour White Required components: F17437\_HEKLA-G2-H




# SAMSUNG

LED LC016D / LC019D / LC026D / LC033D

FWHM / FWTM 26.0° / 47.0°
Efficiency 81 %
Peak intensity 3.4 cd/lm
LEDs/each optic 1
Light colour White

Required components: F17438\_HEKLA-G2-I



# SAMSUNG

 LED
 LC030C/040C G2


 FWHM / FWTM
 25.0° / 45.0°

 Efficiency
 82 %

 Peak intensity
 3.9 cd/lm

 LEDs/each optic
 1

Light colour White Required components: F17438\_HEKLA-G2-I





### SEOUL SEMICONDUCTOR

LED MJT COB LES 14.5

FWHM / FWTM 25.0° / 46.0°
Efficiency 81 %
Peak intensity 3.5 cd/lm
LEDs/each optic 1
Light colour White

Required components: F17438\_HEKLA-G2-I








# **TRIDONIC** SLE G7 LES09

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 26.0° / 42.0° Efficiency 83 % Peak intensity 3.9 cd/lm LEDs/each optic


Light colour White Required components: F17435\_HEKLA-G2-C



# **TRIDONIC**

LED SLE G7 LES15 FWHM / FWTM 25.0° / 46.0° Efficiency 81 % Peak intensity 3.5 cd/lm LEDs/each optic 1 White

Light colour Required components: F17438\_HEKLA-G2-I



Published: 21/10/2020



White

bridgelux

Light colour


LED V13 Gen7

FWHM / FWTM 30.0° / 50.0° Efficiency 86 %

Peak intensity 3.1 cd/lm

LEDs/each optic 1

Required components:



bridgelux

LED V6 HD Gen 7

FWHM / FWTM 30.0° / 42.0°


Efficiency 86 %
Peak intensity 3.7 cd/lm

LEDs/each optic 1

Light colour White

Required components:

F15255\_HEKLA-SOCKET-C



bridgelux

LED Vesta TW 13mm (25W) CSP


FWHM / FWTM 30.0° / 50.0°

Efficiency 86 %

Peak intensity 3.2 cd/lm LEDs/each optic 1

Light colour White

Required components: C16142\_HEKLA-SOCKET-K



bridgelux.

LED Vesta TW 9mm (12W) CSP


FWHM / FWTM 32.0° / 50.0°

Efficiency 87 %
Peak intensity 2.9 cd/lm

LEDs/each optic 1
Light colour White

Required components:

C16142\_HEKLA-SOCKET-K



Published: 21/10/2020



# **CITIZEN**

CLU712/713

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 28.0° / 42.0°


Efficiency 84 %

Peak intensity 3.8 cd/lm

LEDs/each optic White

Light colour

Required components: F17438\_HEKLA-G2-I



#### CREE & LED

LED CHA0304

FWHM / FWTM 30.0° / 41.0°


Efficiency 85 %

Peak intensity 3.8 cd/lm LEDs/each optic 1

White Light colour

Required components:

F17435\_HEKLA-G2-C



#### CREE + LED

LED CHA0410

FWHM / FWTM 30.0° / 41.0°

Efficiency 85 %


Peak intensity 3.9 cd/lm

LEDs/each optic 1

Light colour White

F17435\_HEKLA-G2-C

Required components:



#### CREE - LED

CHA0612

FWHM / FWTM 30.0° / 42.0°


Efficiency 85 %

Peak intensity 3.7 cd/lm LEDs/each optic

White Light colour

Required components:

F17435\_HEKLA-G2-C







LED CMU10xx


 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 27.0° / 44.0° Efficiency 85 %

Peak intensity 3.9 cd/lm

LEDs/each optic

Light colour White

Required components: F17435\_HEKLA-G2-C



#### CREE & LED

LED CXA/B 13xx

FWHM / FWTM 30.0° / 43.0°

Efficiency 85 %


Peak intensity 3.6 cd/lm

LEDs/each optic 1

White Light colour

Required components:

F17439\_HEKLA-G2-J



#### CREE + LED

LED CXA/B 15xx

FWHM / FWTM 28.0° / 42.0°


Efficiency 84 %

Peak intensity 3.8 cd/lm

LEDs/each optic 1

Light colour White

Required components: F17436\_HEKLA-G2-D



#### CREE - LED

CXA/B 1830

FWHM / FWTM 26.0° / 46.0°


Efficiency 83 % Peak intensity 3.6 cd/lm

LEDs/each optic

White Light colour

Required components:

Bender Wirth: 637b Hekla






#### **WNICHIA**

LED NVCWJ024Z-V1MT: COB J-Type Tunable White

FWHM / FWTM 28.0° / 47.0°
Efficiency 85 %
Peak intensity 3.4 cd/lm
LEDs/each optic 1
Light colour White

Required components: C16142\_HEKLA-SOCKET-K Bender Wirth: 498 Typ L8 HV



# **SAMSUNG**

LED LC003D / LC006D / LC009D / LC013D

FWHM / FWTM 26.0° / 43.0°


Efficiency 84 %

Peak intensity 4 cd/lm

LEDs/each optic 1


Light colour White

Required components: F17435\_HEKLA-G2-C



# **TRIDONIC**

LED SLE G7 LES13
FWHM / FWTM 26.0° / 46.0°
Efficiency 83 %
Peak intensity 3.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17438\_HEKLA-G2-I





# PRODUCT DATASHEET CP17412 YASMEEN-70-M-C

#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405, Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

14/14

www.ledil.com/ where\_to\_buy