## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LECONIED NEGO	-/ (1101V (10) 2013/ 2	to to energy	By labelling of light
Supplier's name	or trade mark:	Böhmer Leuchten		
Supplier's addres	ss: Böhmer-Leu	chten, Lüttkewiese	n 11, 59757 Müschede A	rnsberg HSK, DE
Model identifier	: 34097			
Type of light sou	rce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)		matt cover		
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein
Colour-tuneable light source:		Nein	Envelope:	-
High luminance light source:		Nein		
Anti-glare shield:		Nein	Dimmable:	No
		Product para	meters	
Parameter		Value	Parameter	Value
		General product	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		12	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P <sub>on</sub> ), expressed in W		12,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
	Height	70	Spectral power	See image
dimensions	Width	90	distribution in the	in last page
without	Depth	130		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	- -			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	80	Survival factor	0,95			
the lumen maintenance factor	0,95					

(a)'-': not applicable; (b)'-': not applicable;