

## Datasheet for part number CA06COME28-16PB

Our Catalog Part Number: CA06COM-E28-16P-B

Our Global Manufacturing Part Number: 121534-0018

Brand: Cannon Product Category: Circular Product Line: CA Bayonet Series: CA COM-B

| Product Datasheet  |  |
|--|--|
| Bayonet  | Connector with Bayonet Coupling  |
| Shell Style  | Plug, straight   |
| Endbell Style  | Endbell with clamp and bushing (w/o grommet and ferrule)   |
| Gender   | Pin  |
| Shell Size   | 28   |
| Contact Arrangement                                      | 28-16  |
| Number of contacts                                       | 20 contacts size 16  |
| Contact Type   | Solder Cup   |
| Contact Plating  | Hard silver  |
| Contacts installed                                       | yes  |
| Contact Rating at +20 °C (68 °F)<br>(Size 15/15S/16/16S) | 22 A   |
| Contact Resistance<br>(Size 15/15S/16/16S)               | 6 mΩ   |
| Operating Voltage  | In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41.                     |
| Insulator Resistance                                     | ≥1000 MΩ   |
| Test Voltage   | 1600 Vrms  |
| Air and Creepage Paths (Min)                             | 1,1 mm   |
| Ambient Temperature                                      | Standard insulator material -55°/+125°C (-67/257°F)  |
| Safety Provisions  | IP67 (only applies if a grommet is used)   |
| Mating Cycles  | 500 min  |
| Sep. Force per Contact<br>(Size 15/15S/16/16S)           | 1,0 N  |
| Gage   | For infos on Gage please see catalog VG95234, part 1   |
| Coupling Torque  | Closing: 7 Nm max / Opening: 0,92 Nm min   |
| Contact Retention<br>(Size 15/15S/16/16S)                | 35 N   |
| Shell Material   | Aluminium alloy  |
| Shell Plating  | Nickel plated  |
| Insulator and Gromet Material                            | CR-Elastomere  |
| Contact Material   | Copper alloy   |
| Harnessing Info: Contact Cross-Section                   | See assembly instruction   |
| Harnessing Info: Insulator Diameter                      | See assembly instruction   |
| Wire Stripping<br>(Size 15/15S/16/16S)                   | 6,2 mm   |
| General Info   | All tests in accordance with VG95319 and/or if applicable with VG95210 except salt spray resistance and heat and humidity endurance test |