


			Conditions	Diagrams
cell type:	NiMH			
cell size:	D			
nominal voltage:	1.2	V		
max. charge voltage:	1.5	V	at standard charge (0.1C / 20°C)	
capacity				
nominal:	9000	mAh	discharge at 0.2C	
minimum:	8500	mAh	discharge at 0.2C	
	7650	mAh	discharge at 1C	
			1.0V end discharge voltage	
			ta: 20°C	
max. continuous discharge current:	24	A	ta: 0...45°C	
charge	current	time		
standard charge:	900	mA	14...16hrs	
quick charge:	2500	mA	4hrs	
fast charge:	4500	mA	2.2hrs	
recommended charge	0...5	mV	- delta V	
termination control	0.8...1	°C	temperature rise per minute	
parameters:	45...50	°C	TCO (temperature cut off)	
trickle charge current:	85...285	mA	(recommended)	
continuous overcharge: (less than 28 days)	≤ 850	mA	no conspicuous deformation no leakage	
internal resistance: (impedance)	≤ 6	mΩ	at 1KHz battery fully charged	
life expectance:	≥ 500	cycles	acc. IEC standard	
self discharge				
charge retention:	≥ 80	%	after 6 months storage	
(ta: 20°C)	≥ 75	%	after 12 months storage	
initial capacity:	≥ 6000	mAh	within 30 days after delivery discharge at 0.2C	
ambient temperature range:	0...45	°C	standard charge	
	10...40	°C	fast charge	
	- 20...55	°C	discharge	
	- 20...50	°C	storage (≤3months)	
	- 20...40	°C	storage (≤6months)	
	- 20...30	°C	storage (≤24months)	
QCT1:	10/8300/25			
QCT2:	12/8000/30			
mechanical specifications				
cell dimensions				
diameter d1:	33.0 - 0.8	mm		
diameter d2:	approx. 12.0	mm		
height h1:	61.0 - 1.5	mm		
height h2:	0.0 - 0.5	mm		
weight:	160 ± 5	g		
				
				
				
			tags	
			material: Fe, Nickel plated	
			length: 40mm	
			width: 6mm	
			thickness: 0.15mm	
	ANSMANN Specifications for model:		D9000mAh RTU-type FLAT TOP with tags (Z-form) in plastic bag	
	data sheet no. / part no.		2314-3003	
	version no.		0	
	author / date		TG/ 13.01.2013	