

MINITWS Acoustic Warning Device




RND 430-00101 (24V)



RND 430-00102 (240V)

Dispositivo di segnalazione acustica.

Acoustic warning device.
Dispositif de signalisation
acoustique. Akustikmodul.
Zumbador.

| CORPO BODY CORPS GEHAUSE CUERPO DEL PRODUCTO | PC | | | | | | | | |
|---|---|--------|---------|--------|---------|------|----|-----|----|
| GHIERA RING BAGUE RING CONTERA | PC | | | | | | | | |
| GRUPPO ACUSTICO ACOUSTIC SOURCE SOURCE ACOUSTIQUE SCHALLQUELLE FUENTE SONORA | Trasduttore magneto-dinamico 8 ohm 8 ohm Magneto-dynamic transducer Transducteur magnéto-dynamique 8 ohm 8 Ohm Magneto-dynamischer Wandler Convertidor magneto-dinámico de 8 ohmios | | | | | | | | |
| COLORI DISPONIBILI AVAILABLE COLOURS COULEURS DISPONIBLES VERFÜGBARE FARBEN COLORES DISPONIBLES |  | | | | | | | | |
| TENSIONE DI ALIMENTAZIONE VOLTAGE TENSION SPANNUNG TENSIÓN | 24 Vdc/Vac - 240 Vac | | | | | | | | |
| SERVIZIO OPERATION FONCTIONNEMENT BETRIEBSART FUNCIONAMIENTO | ∞ | | | | | | | | |
| CORRENTE NOMINALE CURRENT CONSUMPTION CONSOMMATION DE COURANT STROMAUFNAHME CONSUMO DE CORRIENTE | <table border="1"> <thead> <tr> <th></th> <th>24 Vdc</th> <th>24 Vac</th> <th>240 Vac</th> </tr> </thead> <tbody> <tr> <td>(mA)</td> <td>40</td> <td>130</td> <td>15</td> </tr> </tbody> </table> | | 24 Vdc | 24 Vac | 240 Vac | (mA) | 40 | 130 | 15 |
| | 24 Vdc | 24 Vac | 240 Vac | | | | | | |
| (mA) | 40 | 130 | 15 | | | | | | |
| RESA ACUSTICA ACOUSTIC OUTPUT RENDEMENT ACOUSTIQUE SCHALLLEISTUNGSPEGEL SALIDA ACUSTICA | 77 dB(A)1m | | | | | | | | |
| MODALITA' SUONO SOUND EFFECT EFFET ACOUSTIQUE SOUND- EFFEKT EFECTOS DE SONIDO | BITONALE 800/1000 HZ DUAL TONE BITONAL | | | | | | | | |
| GRADO IP IP RATING DEGRE IP SCHUTZART GRADO IP | IP54 | | | | | | | | |

MINITWS Acoustic Warning Device



| | |
|---|--|
| TEMPERATURA DI FUNZIONAMENTO <i>OPERATING TEMPERATURE TEMPERATURE DE SERVICE BETRIEBSTEMPERATUR TEMPERATURA DE FUNCIONAMIENTO</i> | -30°C+50°C |
| VIBRAZIONI <i>VIBRATIONS VIBRATIONS VIBRATIONEN VIBRACIONES</i> | INDUSTRIAL CEI 60068-2-6 SINE |
| CERTIFICAZIONI, OMOLOGAZIONI <i>CERTIFICATIONS, APPROVALS CERTIFICACIONES, HOMOLOGATIONS PRODUKTZERTIFIKATE, ZULASSUNGEN CERTIFICADOS, HOMOLOGACIONES</i> | CE, UKCA |
| FISSAGGIO <i>MOUNTING FIXATION FIXIERUNG FIJACIÓN</i> | GHIERA <i>RING BAGUE RING CONTERA</i> |
| DISEGNO <i>TECHNICAL DRAWING DESSIN TECHNISCHE ZEICHNUNG DIBUJO TECNICO</i> | <p>The technical drawing shows a side view of the acoustic warning device. It is a cylindrical component with a textured top surface. Dimension lines indicate a total height of 61 units, an inner diameter of 48 units, and an outer diameter of 55 units.</p> |