



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 18

LOCTITE 4305 LC

SDS No. : 153628
V004.0

Revision: 31.01.2024

printing date: 01.02.2024

Replaces version from: 28.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 4305 LC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Cyanoacrylate

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

| | |
|--|------------|
| Skin irritation | Category 2 |
| H315 Causes skin irritation. | |
| Serious eye irritation | Category 2 |
| H319 Causes serious eye irritation. | |
| Skin sensitizer | Category 1 |
| H317 May cause an allergic skin reaction. | |
| Specific target organ toxicity - single exposure | Category 3 |
| H335 May cause respiratory irritation. | |
| Target organ: respiratory tract irritation | |

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Ethyl 2-cyanoacrylate

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Signal word:

Warning

Hazard statement:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Supplemental information

Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

**Precautionary statement:
Prevention**

P261 Avoid breathing vapors.
P280 Wear protective gloves/eye protection.

**Precautionary statement:
Response**

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Precautionary statement:
Disposal**

P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number REACH-Reg No. | Concentration | Classification | Specific Conc. Limits, M-factors and ATEs | Add. Information |
|--|---|--|---|------------------|
| Ethyl 2-cyanoacrylate 7085-85-0 230-391-5 01-2119527766-29 | 50- 100 % | Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 | STOT SE 3; H335; C >= 10 % | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 423-340-5 01-2119489401-38 01-2119936813-33 | 0,1- < 1 % | Skin Sens. 1A, H317 Aquatic Chronic 4, H413 | | |
| Hydroquinone 123-31-9 204-617-8 01-2119524016-51 | 0,01- < 0,1 % | Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Carc. 2, H351 Muta. 2, H341 Acute Tox. 4, Oral, H302 Eye Dam. 1, H318 Skin Sens. 1, H317 | M acute = 10 M chronic = 1 | |
| Dicyclopentadienyl iron 102-54-5 203-039-3 | 0,0025- < 0,025 % (25 ppm- < 250 ppm) | Flam. Sol. 1, H228 Acute Tox. 4, Oral, H302 Aquatic Chronic 1, H410 STOT RE 1, H372 Repr. 1B, H360 | M chronic = 10 | |

**If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth.

Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn.

Burns should be treated normally after the adhesive has been removed from the skin.

Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water.

Eye contact:

If the eye is bonded closed, release eyelashes with warm water by covering with wet pad.

Keep eye covered until debonding is complete, usually within 1-3 days.

Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive.

Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.

Ingestion:

Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

Fine water spray

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ventilation (low level) is recommended when using large volumes

Use of dispensing equipment is recommended to minimise the risk of skin or eye contact

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.
Refer to Technical Data Sheet

7.3. Specific end use(s)

Cyanoacrylate

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|-----------------------------------|--|-----------------|
| Ethyl 2-cyanoacrylate 7085-85-0 [ETHYL CYANOACRYLATE] | 0,3 | 1,5 | Short Term Exposure Limit (STEL): | 15 minutes | EH40 WEL |
| Hydroquinone 123-31-9 [HYDROQUINONE] | | 0,5 | Time Weighted Average (TWA): | | EH40 WEL |
| Ferrocene 102-54-5 [Dust, respirable dust] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Ferrocene 102-54-5 [Dust, inhalable dust] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |

Occupational Exposure Limits

Valid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|-----------------------------------|--|-----------------|
| Ethyl 2-cyanoacrylate 7085-85-0 [ETHYL 2-CYANOACRYLATE; ETHYL CYANOACRYLATE] | 1 | | Short Term Exposure Limit (STEL): | 15 minutes | IR_OEL |
| Ethyl 2-cyanoacrylate 7085-85-0 [ETHYL 2-CYANOACRYLATE; ETHYL CYANOACRYLATE] | 0,2 | | Time Weighted Average (TWA): | | IR_OEL |
| Hydroquinone 123-31-9 [HYDROQUINONE] | | 0,5 | Time Weighted Average (TWA): | | IR_OEL |
| Ferrocene 102-54-5 [FERROCENE (DICYCLOPENTADIENYL IRON)] | | 10 | Time Weighted Average (TWA): | | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|---|------------------------------------|--------------------|------------------|-----|------------------|--------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7 | aqua (freshwater) | | 0,001 mg/l | | | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7 | aqua (intermittent releases) | | 0,001 mg/l | | | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7 | aqua (marine water) | | 0,001 mg/l | | | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7 | sewage treatment plant (STP) | | 1 mg/l | | | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7 | sediment (freshwater) | | | | 0,712 mg/kg | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7 | sediment (marine water) | | | | 0,712 mg/kg | | |
| Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7 | Soil | | | | 20 mg/kg | | |
| Hydroquinone 123-31-9 | aqua (freshwater) | | 0,00057 mg/l | | | | |
| Hydroquinone 123-31-9 | aqua (marine water) | | 0,000057 mg/l | | | | |
| Hydroquinone 123-31-9 | sediment (freshwater) | | | | 0,0049 mg/kg | | |
| Hydroquinone 123-31-9 | sediment (marine water) | | | | 0,00049 mg/kg | | |
| Hydroquinone 123-31-9 | aqua (intermittent releases) | | 0,00134 mg/l | | | | |
| Hydroquinone 123-31-9 | Soil | | | | 0,00064 mg/kg | | |
| Hydroquinone 123-31-9 | sewage treatment plant (STP) | | 0,71 mg/l | | | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|---|--------------------|-------------------|---------------------------------------|---------------|------------------------|---------|
| Ethyl 2-cyanoacrylate 7085-85-0 | Workers | Inhalation | Long term exposure - local effects | | 9,25 mg/m ³ | |
| Ethyl 2-cyanoacrylate 7085-85-0 | Workers | Inhalation | Long term exposure - systemic effects | | 9,25 mg/m ³ | |
| Ethyl 2-cyanoacrylate 7085-85-0 | General population | Inhalation | Long term exposure - local effects | | 9,25 mg/m ³ | |
| Ethyl 2-cyanoacrylate 7085-85-0 | General population | Inhalation | Long term exposure - systemic effects | | 9,25 mg/m ³ | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | Workers | Inhalation | Long term exposure - systemic effects | | 21 mg/m ³ | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | Workers | dermal | Long term exposure - systemic effects | | 3 mg/kg | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | General population | inhalation | Long term exposure - systemic effects | | 5,2 mg/m ³ | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | General population | dermal | Long term exposure - systemic effects | | 1,5 mg/kg | |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | General population | oral | Long term exposure - systemic effects | | 1,5 mg/kg | |
| Hydroquinone 123-31-9 | Workers | dermal | Long term exposure - systemic effects | | 3,33 mg/kg | |
| Hydroquinone 123-31-9 | Workers | inhalation | Long term exposure - systemic effects | | 2,1 mg/m ³ | |
| Hydroquinone 123-31-9 | General population | dermal | Long term exposure - systemic effects | | 1,66 mg/kg | |
| Hydroquinone 123-31-9 | General population | inhalation | Long term exposure - systemic effects | | 1,05 mg/m ³ | |
| Hydroquinone 123-31-9 | General population | oral | Long term exposure - systemic effects | | 0,6 mg/kg | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:
Ensure good ventilation/extraction.

Respiratory protection:
Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Polyethylene or polypropylene gloves are recommended when using large volumes.

Do not use PVC, rubber or nylon gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|---|---|
| Delivery form | liquid |
| Colour | Colorless |
| Odor | irritating |
| Physical state | liquid |
| Melting point | Not applicable, Product is a liquid |
| Solidification temperature | -22 °C (-7.6 °F) |
| Initial boiling point | > 149 °C (> 300.2 °F)None |
| Flammability | The product is not flammable. |
| Explosive limits | Not applicable, The product is not flammable. |
| Flash point | 80 - 93 °C (176 - 199.4 °F); None |
| Auto-ignition temperature | Not applicable, The product is not flammable. |
| Decomposition temperature | Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use |
| pH | Not applicable, Product is non-soluble (in water). |
| Viscosity (kinematic) (25 °C (77 °F);) | 560 - 1.120 mm ² /s |
| Solubility (qualitative) (20 °C (68 °F); Solvent: Water) | Polymerises in presence of water. |
| Partition coefficient: n-octanol/water | Not applicable |
| Vapour pressure (20 °C (68 °F)) | Mixture < 0,3 mbar |
| Vapour pressure (50 °C (122 °F)) | < 700 mbar;no method / method unknown |
| Density (20 °C (68 °F)) | 1,1 g/cm ³ None |
| Relative vapour density: (20 °C) | 3 Heavier than air |

Particle characteristics

Not applicable
Product is a liquid**9.2. Other information**

Other information not applicable for this product

SECTION 10: Stability and reactivity**10.1. Reactivity**

Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information**General toxicological information:**

Cyanoacrylates are considered to have relatively low toxicity. Acute oral LD50 is >5000mg/kg (rat). It is almost impossible to swallow as it rapidly polymerises in the mouth.

Prolonged exposure to high concentrations of vapours may lead to chronic effects in sensitive individuals

In dry atmosphere with < 50% humidity, vapours may irritate the eyes and respiratory system

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|---------------|---------|---|
| Ethyl 2-cyanoacrylate 7085-85-0 | LD50 | > 5.000 mg/kg | rat | equivalent or similar to OECD Guideline 423 (Acute Oral toxicity) |
| Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Hydroquinone 123-31-9 | LD50 | 367 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Dicyclopentadienyl iron 102-54-5 | LD50 | 1.320 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|------------|---------------|---------|---|
| Ethyl 2-cyanoacrylate 7085-85-0 | LD50 | > 2.000 mg/kg | rabbit | equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity) |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| Hydroquinone 123-31-9 | LD50 | > 2.000 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |
| Dicyclopentadienyl iron 102-54-5 | LD50 | > 3.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

Bonds skin in seconds. Considered to be of low toxicity: acute dermal LD50 (rabbit)>2000mg/kg
Due to polymerisation at the skin surface allergic reaction is unlikely to occur

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|-------------------------------------|---------------------|---------------|---------|---|
| Ethyl 2-cyanoacrylate 7085-85-0 | slightly irritating | 24 h | rabbit | equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Hydroquinone 123-31-9 | not irritating | 24 h | rabbit | Weight of evidence |
| Dicyclopentadienyl iron 102-54-5 | not irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

Liquid product will bond eyelids. In a dry atmosphere (RH<50%) vapours may cause irritation and lachrymatory effect

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|-------------------------------------|----------------|---------------|---------|--|
| Ethyl 2-cyanoacrylate 7085-85-0 | irritating | | rabbit | equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Dicyclopentadienyl iron 102-54-5 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|-------------------------------------|-----------------|------------------------------------|------------|--|
| Ethyl 2-cyanoacrylate 7085-85-0 | not sensitising | Skin sensitisation | guinea pig | not specified |
| Hydroquinone 123-31-9 | sensitising | Guinea pig maximisation test | guinea pig | equivalent or similar to OECD Guideline 406 (Skin Sensitisation) |
| Hydroquinone 123-31-9 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| Dicyclopentadienyl iron 102-54-5 | not sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|----------------------------------|----------|--|--------------------------------------|---------|---|
| Ethyl 2-cyanoacrylate 7085-85-0 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Ethyl 2-cyanoacrylate 7085-85-0 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Ethyl 2-cyanoacrylate 7085-85-0 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Hydroquinone 123-31-9 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Hydroquinone 123-31-9 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Hydroquinone 123-31-9 | positive | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Dicyclopentadienyl iron 102-54-5 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Dicyclopentadienyl iron 102-54-5 | negative | in vitro mammalian chromosome aberration test | with and without | | equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Dicyclopentadienyl iron 102-54-5 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Hydroquinone 123-31-9 | positive | intraperitoneal | | mouse | equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| Hydroquinone 123-31-9 | negative | oral: gavage | | rat | equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test) |
| Hydroquinone 123-31-9 | positive | intraperitoneal | | mouse | equivalent or similar to OECD Guideline 483 (Mammalian Spermatogonial Chromosome Aberration Test) |
| Dicyclopentadienyl iron 102-54-5 | negative | oral: unspecified | | mouse | EU Method B.12 (Mutagenicity) |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|------------------------------|--------------|----------------------|--|---------|-------------|--|
| Hydroquinone 123-31-9 | carcinogenic | oral: gavage | 103 w 5 d/w | rat | male/female | equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |
| Hydroquinone 123-31-9 | carcinogenic | oral: gavage | 103 w 5 d/w | mouse | female | equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|-------------------------------------|--|----------------------|----------------------|---------|--|
| Hydroquinone 123-31-9 | NOAEL P 15 mg/kg NOAEL F1 150 mg/kg NOAEL F2 150 mg/kg | Two generation study | oral: gavage | rat | EPA OTS 798.4700 (Reproduction and Fertility Effects) |
| Dicyclopentadienyl iron 102-54-5 | NOAEL P 10 mg/kg NOAEL F1 10 mg/kg | screening | oral: gavage | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|-------------------------------------|------------------|----------------------|--|---------|--|
| Hydroquinone 123-31-9 | NOAEL 50 mg/kg | oral: gavage | 13 w 5 d/w | rat | not specified |
| Hydroquinone 123-31-9 | NOAEL 73,9 mg/kg | dermal | 13 w 6 h/d, 5 d/w | rat | equivalent or similar to OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) |
| Dicyclopentadienyl iron 102-54-5 | LOAEL 30 mg/kg | oral: capsule | 180 d daily | dog | not specified |
| Dicyclopentadienyl iron 102-54-5 | NOAEL 5 mg/kg | oral: gavage | 28 d daily | rat | OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents) |

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information**General ecological information:**

Biological and Chemical Oxygen Demands (BOD and COD) are insignificant.
Do not empty into drains / surface water / ground water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|------------------------------|---------------|--------------------------|--|
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | LC50 | Toxicity > Water solubility' | 96 h | Danio rerio | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Hydroquinone 123-31-9 | LC50 | 0,638 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Dicyclopentadienyl iron 102-54-5 | LC50 | 24,5 mg/l | 48 h | Leuciscus idus melanotus | OECD Guideline 203 (Fish, Acute Toxicity Test) |

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|-----------------------------|---------------|---------------|--|
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | EC50 | Toxicity > Water solubility | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Hydroquinone 123-31-9 | EC50 | 0,134 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Dicyclopentadienyl iron 102-54-5 | EC50 | > 1,5 - 2,5 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|-----------------------------|---------------|---------------|---|
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | NOEC | Toxicity > Water solubility | 21 day | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Hydroquinone 123-31-9 | NOEC | 0,0057 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Dicyclopentadienyl iron 102-54-5 | NOEC | 0,002 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|-----------------------------|---------------|--|---|
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | EC50 | Toxicity > Water solubility | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | NOEC | Toxicity > Water solubility | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Hydroquinone 123-31-9 | EC50 | 0,335 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Dicyclopentadienyl iron 102-54-5 | EC50 | 1,03 mg/l | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Dicyclopentadienyl iron 102-54-5 | EC10 | 0,14 mg/l | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|------------|---------------|---------|--|
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | EC 50 | > 100 mg/l | 3 h | | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| Hydroquinone 123-31-9 | EC 50 | 0,038 mg/l | 30 min | | not specified |

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|---|----------------------------|-----------|---------------|---------------|--|
| Ethyl 2-cyanoacrylate 7085-85-0 | not readily biodegradable. | aerobic | 57 % | 28 d | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | not readily biodegradable. | aerobic | 1 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| Hydroquinone 123-31-9 | readily biodegradable | aerobic | 75 - 81 % | 30 d | EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test) |
| Dicyclopentadienyl iron 102-54-5 | not readily biodegradable. | aerobic | 56 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| Dicyclopentadienyl iron 102-54-5 | inherently biodegradable | aerobic | 73 % | 41 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Bioconcentration factor (BCF) | Exposure time | Temperature | Species | Method |
|---|-------------------------------|---------------|-------------|---------|---|
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | < 5 | | | | OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish) |

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---|--------|-------------|--|
| Ethyl 2-cyanoacrylate 7085-85-0 | 0,776 | 22 °C | EU Method A.8 (Partition Coefficient) |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | 5,8 | | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| Hydroquinone 123-31-9 | 0,59 | | EU Method A.8 (Partition Coefficient) |
| Dicyclopentadienyl iron 102-54-5 | 3,711 | 22 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | PBT / vPvB |
|---|---|
| Ethyl 2-cyanoacrylate 7085-85-0 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 162881-26-7 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Hydroquinone 123-31-9 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorised landfill or incinerate under controlled conditions.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | 3334 |

14.2. UN proper shipping name

| | |
|------|---|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Aviation regulated liquid, n.o.s. (Cyanoacrylate ester) |

14.3. Transport hazard class(es)

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | 9 |

14.4. Packing group

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | III |

14.5. Environmental hazards

| | |
|------|----------------|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

14.6. Special precautions for user

| | |
|-----|----------------|
| ADR | not applicable |
|-----|----------------|

| | |
|------|---|
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | Primary packs containing less than 500ml are unregulated by this mode of transport and may be shipped unrestricted. |

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|---|----------------|
| Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): | Not applicable |
| Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): | Not applicable |
| Persistent organic pollutants (Regulation (EU) 2019/1021): | Not applicable |
| VOC content (2010/75/EC) | < 3 % |

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H228 Flammable solid.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H360 May damage fertility or the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

| | |
|-------------|---|
| ED: | Substance identified as having endocrine disrupting properties |
| EU OEL: | Substance with a Union workplace exposure limit |
| EU EXPLD 1: | Substance listed in Annex I, Reg (EC) No. 2019/1148 |
| EU EXPLD 2: | Substance listed in Annex II, Reg (EC) No. 2019/1148 |
| SVHC: | Substance of very high concern (REACH Candidate List) |
| PBT: | Substance fulfilling persistent, bioaccumulative and toxic criteria |
| PBT/vPvB: | Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria |
| vPvB: | Substance fulfilling very persistent and very bioaccumulative criteria |

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

Annex - Exposure Scenarios:

Exposure Scenarios for ethyl 2-cyanoacrylate can be downloaded under the following link:
<https://mysds.henkel.com/index.html#/appSelection>