



CONNECTION CABLE; LENGTH 0,1M; FLAT;  
 CONNECTION OF BASIC UNIT TO CURRENT  
 MEASURING MODULE, CURRENT/VOLTAGE  
 MEASUR. MODULE, OPERATOR PANEL OR TO  
 EXPANSION MODULES VIA SYSTEM INTERFACE

General technical data:		
product brand name		SIRIUS
Product designation		connecting cable
Design of the product		<kein Wert>
Protection class IP		<kein Wert>
Ambient temperature		
• during storage	°C	-40 ... +80
• during operation	°C	-25 ... +60
• during transport	°C	-40 ... +80
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750		<kein Wert>
Equipment marking acc. to DIN EN 61346-2		<kein Wert>
Certificates/ approvals:		

General Product Approval	EMC	Test Certificates
--------------------------	-----	-------------------



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)

Shipping Approval	other
-------------------	-------



[Confirmation](#)

other
-------

[PROFISafe-Certification](#)

[PROFINET-Certification](#)



Profibus

Further information
---------------------

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrymall>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF79310AA000>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3UF79310AA000>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3UF79310AA000&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF79310AA000&lang=en)

