

#### 12500 TI Boulevard, MS 8640, Dallas, Texas 75243

## PCN# 20230502001.1 Qualify New Assembly Material set for Selected Device(s)

Change Notification / Sample Request

**Date:** May 08, 2023 **To:** Newark/Farnell PCN

#### Dear Customer:

This is an announcement of a change to a device that is currently offered by Texas Instruments. The details of this change are on the following pages.

Texas Instruments requires acknowledgement of receipt of this notification within 30 days of the date of this notice. Lack of acknowledgement of this notice within 30 days constitutes acceptance of the change. If samples or additional data are required, requests must be received within 30 days of this notification.

The changes discussed within this PCN will not take effect any earlier than the proposed first ship date on Page 3 of this notification, unless customer agreement has been reached on an earlier implementation of the change.

This notice does not change the end-of-life status of any product. Should product affected be on a previously issued product withdrawal/discontinuance notice, this notification does not extend the life of that product or change the life time buy offering/discontinuance plan.

For questions regarding this notice or to provide acknowledgement of this PCN, you may contact your local Field Sales Representative or the PCN Team (PCN www admin team@list.ti.com). For sample requests or sample related questions, contact your local Field Sales Representative.

Sincerely,

PCN Team SC Business Services

### 20230502001.1 Attachment: 1

#### **Products Affected:**

The devices listed on this page are a subset of the complete list of affected devices. According to our records, these are the devices that you have purchased within the past twenty-four (24) months. The corresponding customer part number is also listed, if available.

**DEVICE** AMC 1305M05DW **CUSTOMER PART NUMBER** 

null

Technical details of this Product Change follow on the next page(s).

PCN	Number:	20230502001	.1	PC	N Date:	May 08, 2023			
Title	Qualify New A	Assembly Mate	rial set for	)					
Cust	tomer Contact:	PCN Manager	Dept:		Quality Ser	vices			
Duan	acced 1St Chin Date	A 00 20	.22	Samp	le requests	,			
Prop	oosed 1 <sup>st</sup> Ship Date	e: Aug 08, 20	epted until:						
*Saı	mple requests rec	eived after Ju	ne 08, 20	23 w	Il not be su	ppor	ted.		
Cha	nge Type:								
	Assembly Site		Design				Vafer Bum	p Site	
$\boxtimes$	Assembly Process		Data Sh	eet			Wafer Bump Material		
$\boxtimes$	Assembly Materials		Part nur		hange			p Process	
	Mechanical Specific		Test Site			_	Vafer Fab		
Ш	Packing/Shipping/L	abeling L	Test Pro	cess			Vafer Fab		
						ШΙ	Vafer Fab	Process	
			PCN E	<u> eta i</u>	S				
Desc	cription of Change	:							
Texas Instruments is pleased to announce the qualification of new assembly material for devices listed in "Product affected" section below. Devices will remain in current assembly facility and piece part changes as follows:									
Grou	up 1 Device:								
	Materia			rent			Proposed		
	Wire typ	e	0.96r	nil Au			0.8mil Cu		
Grou	ıp 2 Device:								
	Materia	nl	Current				Proposed		
	Wire typ	oe e	0.96mil Au				0.8mil Cu		
	Mold compo	ound	420	9640			4221499		
Grou	ıp 3 Device:								
	Materia	nl .	Cur	re nt			Proposed		
	Wire typ	e	0.96r	nil Au			0.8mil Cu		
	Mount compound		404	2500			4211470		
	Mold compound		4209640			4221499			
		<u>'</u>							
Reas	son for Change:								
Cont	inuity of supply.								
1) T	o align with world to	echnology trend	ds and use	wiring	ı with enhan	ced n	nechanical	and	
е	lectrical properties								
	laximize flexibility w	ithin our Asser	nblv/Test	produc	tion sites.				
,	Cu is easier to obtain			p. Jauc					
	cipated impact on		nction O	ua litv	or Reliabili	ty (n	ositive /	negative):	
		Tom, Tit, Pu	nction, Q	uanty	or izeliabili	cy (P	OSILIVE /	negative).	
None		stal Datings							
шр	act on Environme	itai Katifiys							
	ked boxes indicate age. If below boxes ags.				-				
	RoHS	REAC	СН		Green Statu	S	IEC	62474	
	No Change	⊠ No Chang			lo Change		M No Ch		

None

#### **Product Affected:**

### Group 1:

AMC1204BDW	AMC1304L25DW	AMC1305F25DW	AMC1305M25DW
AMC1204BDWR	AMC1304L25DWR	AMC1305F25DWR	AMC1305M25DWR
AMC1204DW	AMC1304M05DW	AMC1305L25DW	AMC1307M05DWR
AMC1204DWR	AMC1304M05DWR	AMC1305L25DWR	
AMC1304L05DW	AMC1304M25DW	AMC1305M05DW	
AMC1304L05DWR	AMC1304M25DWR	AMC1305M05DWR	

### Group 2:

ISO1050DW	ISO7331CDWR	ISO7341CDW	ISO7342FCDWR
ISO1050DWR	ISO7331FCDW	ISO7341CDWR	ISO7520CDW
ISO7330CDW	ISO7331FCDWR	ISO7341FCDW	ISO7520CDWR
ISO7330CDWR	ISO7340CDW	ISO7341FCDWR	ISO7521CDW
ISO7330FCDW	ISO7340CDWR	ISO7342CDW	ISO7521CDWR
ISO7330FCDWR	ISO7340FCDW	ISO7342CDWR	SN1007074DW
ISO7331CDW	ISO7340FCDWR	ISO7342FCDW	SN1007074DWR

## **Group 3:**

ISO7631FCDW	ISO7631FMDWR	ISO7641FCDW	ISO7641FMDWR
ISO7631FCDWR	ISO7640FMDW	ISO7641FCDWR	
ISO7631FMDW	ISO7640FMDWR	ISO7641FMDW	

# **Qualification Report**

Automotive New Product Qualification Summary (As per AEC-Q100 and JEDEC Guidelines) Approve Date 28-Apr-2023

### **Qualification Results**

Data Displayed as: Number of lots / Total sample size / Total failed

					,			,			
Туре	#	Test Spec	Min Lot Qty	SS / Lot	Test Name	Condition	Duration	Qual Device: AMC1305M25QDWQ1	Qual Device: AMC1305M25QDWQ1	QBS Reference: AMC1305M25QDWRQ1	QBS Reference: AMC1305M25QDWRQ1
Test Group	est Group A - Accelerated Environment Stress Tests										
PC	A1	JEDEC J- STD-020 JESD22- A113	3	77	Preconditioning	MSL3 260C	1 Step	No Fails	No Fails	No Fails	No Fails
HAST	A2	JEDEC JESD22- A110	3	77	Biased HAST	130C/85%RH	96 Hours	-	-	3/231/0	3/231/0
AC/UHAST	А3	JEDEC JESD22- A102/JEDEC JESD22- A118	3	77	Autoclave	121C/15psig	96 Hours	3/231/0	3/231/0	3/231/0	3/231/0
тс	A4	JEDEC JESD22- A104 and Appendix 3	3	77	Temperature Cycle	-65C/150C	500 Cycles	3/231/0	3/231/0	3/231/0	3/231/0
TC-BP	A4	MIL-STD883 Method 2011	1	5	Post Temp Cycle Bond Pull	-	-	1/5/0	1/5/0	1/5/0	1/5/0

HTSL	A6	JEDEC JESD22- A103	1	45	High Temperature Storage Life	150C	1000 Hours	3/135/0	3/135/0	1/45/0	-
HTSL	A6	JEDEC JESD22- A103	1	45	High Temperature Storage Life	175C	500 Hours	-	-		1/45/0
Test Group	B - Acce	elerated Lifetime	e Simula	tion Tes	ts						
HTOL	B1	JEDEC JESD22- A108	1	77	Life Test	150C	408 Hours	-	-	1/77/0	3/231/0
ELFR	B2	AEC Q100- 008	1	77	Early Life Failure Rate	150C	24 Hours	-	-		3/2400/0
Test Group	C - Pack	age Assembly	Integrity	Tests							
WBS	C1	AEC Q100- 001	1	30	Wire Bond Shear	Minimum of 5 devices, 30 wires Cpk>1.67	Wires	3/90/0	3/90/0	3/90/0	3/90/0
WBP	C2	MIL-STD883 Method 2011	1	30	Wire Bond Pull	Minimum of 5 devices, 30 wires Cpk>1.67	Wires	3/90/0	3/90/0	3/90/0	3/90/0
SD	СЗ	JEDEC J- STD-002	1	15	PB Solderability	>95% Lead Coverage	-	-	-	1/15/0	-
SD	СЗ	JEDEC J- STD-002	1	15	PB-Free Solderability	>95% Lead Coverage	-	-	-	1/15/0	1/15/0
PD	C4	JEDEC JESD22- B100 and B108	1	10	Physical Dimensions	Cpk>1.67				3/30/0	3/30/0
Test Group	D - Die F	abrication Relia	ability Te	sts							
ЕМ	D1	JESD61	-	-	Electromigration	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
TDDB	D2	JESD35	-	-	Time Dependent Dielectric Breakdown		-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
нсі	D3	JESD60 & 28	-	-	Hot Carrier Injection	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
NBTI	D4	-	-	-	Negative Bias Temperature Instability	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
SM	D5	-	-	-	Stress Migration	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
Test Group	E - Elect	rical Verification	n Tests								
ESD	E2	AEC Q100- 002	1	3	ESD HBM	-	2000 Volts			1/3/0	1/3/0
ESD	E3	AEC Q100- 011	1	3	ESD CDM		500 Volts		-	1/3/0	1/3/0
LU	E4	AEC Q100- 004	1	6	Latch-Up	Per AEC Q100-004	-	-	-	1/6/0	1/6/0
ED	E5	AEC Q100- 009	3	30	Electrical Distributions	Cpk>1.67 Room, hot, and cold	-	3/90/0	3/90/0	3/90/0	3/90/0
	11.41		-		for Autoala			CT_TUD/Diag	LILAGE E	a a made coma Correla .	The arrest of Cheerals

Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable

The following are equivalent HTOL options based on an activation energy of  $0.7eV: 125C/1 \, k$  Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours

The following are equivalent HTSL options based on an activation energy of  $0.7 \, \text{eV}$ :  $150 \, \text{C/1k}$  Hours, and  $170 \, \text{C/420}$  Hours

The following are equivalent Temp Cycle options per JESD47: -55C/125C/700 Cycles and -65C/150C/500 Cycles Ambient Operating Temperature by Automotive Grade Level:

Grade 0 (or E): -40C to +150C Grade 1 (or Q): -40C to +125C Grade 2 (or T): -40C to +105C Grade 3 (or I): -40C to +85C

E1 (TEST): Electrical test temperatures of Qual samples (High temperature according to Grade level):

Room/Hot/Cold: HTOL, ED

Room/Hot: THB/HAST, TC/PTC, HTSL, ELFR, ESD & LU

Room: AC/uHAST

Quality and Environmental data is available at TI's external Web site: http://www.ti.com/

For questions regarding this notice, e-mails can be sent to the regional contacts shown below or your local Field Sales Representative.

Location	E-Mail
WW PCN Team	PCN ww admin team@list.ti.com

#### IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disdaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.