

EASY FOAM (600ML) {FROM EXP 28082018}

Page: 1

Compilation date: 19/02/2014

**Revision date: 24/07/2019** 

Revision No: 3.1

#### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: EASY FOAM (600ML) {FROM EXP 28082018}

REACH registered number(s): EXEMPT - MIXTURE

Product code: 135

**UFI:** \* GJSW-R01E-381H-F15W

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: \* Air Conditioning condenser cleaner PC35: Washing and cleaning products (including

solvent based products).

### 1.3. Details of the supplier of the safety data sheet

Company name: Advanced Engineering Ltd

Guardian House Stroudley Road Basingstoke Hampshire RG24 8NL

**Tel:** +44(0)1256460300

United Kingdom

**Fax:** +44(0)1256462266

Email: sales@advancedengineering.co.uk

#### 1.4. Emergency telephone number

Emergency tel: Advanced Engineering Ltd (24hr) +44 (0) 1256 854318

#### Section 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 2: H223; Skin Corr. 1B: H314; -: H229

Most important adverse effects: Flammable aerosol. Pressurised container: May burst if heated. Causes severe skin

burns and eye damage.

#### 2.2. Label elements

Label elements:

**Hazard statements:** H223: Flammable aerosol.

H229: Pressurised container: May burst if heated.

H314: Causes severe skin burns and eye damage.

Hazard pictograms: GHS02: Flame

GHS05: Corrosion [cont...]

EASY FOAM (600ML) {FROM EXP 28082018}

Page: 2





Signal words: Danger

Precautionary statements: \* P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective clothing, eye protection, face protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Haz. ingredients (label): SODIUM HYDROXIDE

### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture. Heating may cause an

explosion.

PBT: This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

### 3.2. Mixtures

# Hazardous ingredients:

### 1-METHOXY-2-PROPANOL

| EINECS      | CAS       | PBT / WEL  | CLP Classification                      | Percent |  |
|-------------|-----------|--|---|---------|--|
| 203-539-1   | 107-98-2  | -  | Flam. Liq. 3: H226; STOT SE 3: H336     | 1-10%   |  |
| SODIUM HYDR | ROXIDE    |  |   |         |  |
| 215-185-5   | 1310-73-2 | -  | Skin Corr. 1A: H314                     | 1-10%   |  |
| ISOBUTANE   |           |  |   |         |  |
| 200-857-2   | 75-28-5   | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280     | 1-10%   |  |
| 3-BUTOXYPRO | PAN-2-OL  |  |   |         |  |
| 225-878-4   | 5131-66-8 | -  | Eye Irrit. 2: H319; Skin Irrit. 2: H315 | 1-10%   |  |
| BUTANE      |           |  |   |         |  |
| 203-448-7   | 106-97-8  | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280     | 1-10%   |  |

EASY FOAM (600ML) {FROM EXP 28082018}

Page: 3

#### SODIUM LAURYL SARCOSINATE

| 205-281-5 | 137-16-6 | - | Acute Tox. 2: H330; Skin Irrit. 2: H315; | 1-10% |
|-----------|----------|---|--|-------|
|           |          |   | Eye Dam. 1: H318                         |       |

### Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Do not induce vomiting. Wash out mouth with water. If unconscious, check for breathing

and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Give 1 cup of water to drink every 10 minutes. Transfer to hospital

as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If

conscious, ensure the casualty sits or lies down. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in

the recovery position. Consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact. Progressive ulceration will

occur if treatment is not immediate.

Eye contact: \* There may be irritation and pain. The vision may become blurred. The eyes may water

profusely. Corneal burns may occur. May cause permanent damage.

Ingestion: \* Corrosive burns may appear around the lips. Blood may be vomited. There may be

bleeding from the mouth or nose. It is unlikely that this substance will be swallowed due

to its physical properties.

**Inhalation:** \* There may be irritation of the throat with a feeling of tightness in the chest. There may

be drowsiness, slurred speech, muscular weakness, muscle twitching, tremor, blurred

vision, dilated pupils and shock.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure. Drowsiness or mental

confusion may occur.

# 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Water spray. Use water

spray to cool containers.

EASY FOAM (600ML) {FROM EXP 28082018}

Page: 4

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. Corrosive. Vapour may travel considerable distance to source of

ignition and flash back. Forms explosive air-vapour mixture. In combustion emits toxic

fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: \* If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Remove all incompatible

materials as outlined in section 10 of SDS. Eliminate all sources of ignition. Evacuate

the area immediately.

### 6.2. Environmental precautions

**Environmental precautions:** In bulk packaged form, do not discard into Drains, Sewers or surface water courses.

Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Refer to section 13 of SDS for suitable method of

disposal.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

#### Section 7: Handling and storage

### 7.1. Precautions for safe handling

Handling requirements: Use non-sparking tools. Ensure there is sufficient ventilation of the area. Avoid direct

contact with the substance. Smoking is forbidden.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Ensure lighting

and electrical equipment are not a source of ignition. Avoid incompatible materials and

conditions - see section 10 of SDS.

Suitable packaging: Must only be kept in original packaging.

EASY FOAM (600ML) {FROM EXP 28082018}

Page: 5

### 7.3. Specific end use(s)

**Specific end use(s):** \* Air Conditioning condenser cleaner PC35: Washing and cleaning products (including solvent based products).

### Section 8: Exposure controls/personal protection

## 8.1. Control parameters

### **Hazardous ingredients:**

#### 1-METHOXY-2-PROPANOL

#### Workplace exposure limits:

#### Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK    | 375 mg/m3  | 560 mg/m3    | -          | -            |

#### **SODIUM HYDROXIDE**

| UK | - | 2 mg/m3 | - | - |
|----|---|---------|---|---|
|----|---|---------|---|---|

#### **ISOBUTANE**

| UK | 2400 mg/m3 | 9600 mg/m3 | - | - |
|----|------------|------------|---|---|
|    |            |            |   |   |

#### **BUTANE**

| UK | 1450 mg/m3 | 1810 mg/m3 | - | - |
|----|------------|------------|---|---|
|----|------------|------------|---|---|

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: \* Respiratory protection not required.

Hand protection: \* Nitrile gloves. EN 374-1:2003

**Eye protection:** \* Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** \* Impermeable protective clothing.

Environmental: In bulk packaged form, do not discard into Drains, Sewers or surface water courses.

Ensure all engineering measures mentioned in section 7 of SDS are in place.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Aerosol

Odour: Aromatic

Flammability limits %: lower: 1.8 upper: 9.5

Flash point°C: -60 Autoflammability°C: 410 - 580

EASY FOAM (600ML) {FROM EXP 28082018}

Page: 6

#### 9.2. Other information

Other information: Not applicable.

### Section 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: \* Heat. Sources of ignition. Flames. Direct sunlight. Hot surfaces.

### 10.5. Incompatible materials

Materials to avoid: \* Strong oxidising agents. Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion

emits toxic fumes of nitrogen oxides.

### **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

# Hazardous ingredients:

#### 1-METHOXY-2-PROPANOL

| IVN | RAT | LD50 | 4200  | mg/kg |
|-----|-----|------|-------|-------|
| ORL | MUS | LD50 | 11700 | mg/kg |
| ORL | RAT | LDLO | 3739  | mg/kg |

## **SODIUM HYDROXIDE**

| IPR | MUS | LD50 | 40  | mg/kg |
|-----|-----|------|-----|-------|
| ORL | RBT | LDLO | 500 | mg/kg |

#### 3-BUTOXYPROPAN-2-OL

| OLAL | DDT | 1.050 | 0400 | //    |
|------|-----|-------|------|-------|
| SKN  | RBT | LD50  | 3100 | mg/kg |

EASY FOAM (600ML) {FROM EXP 28082018}

Page: 7

#### **SODIUM LAURYL SARCOSINATE**

| DUST/MIST | RAT | LC50 | 0.5 | mg/l  |
|-----------|-----|------|-----|-------|
| ORAL      | RAT | LD50 | 180 | mg/kg |
| VAPOURS   | RAT | LC50 | 1.0 | mg/l  |

### Relevant hazards for product:

| Hazard                        | Route | Basis                 |
|-------------------------------|-------|-----------------------|
| Skin corrosion/irritation     | DRM   | Hazardous: calculated |
| Serious eye damage/irritation | OPT   | Hazardous: calculated |

#### Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact. Progressive ulceration will

occur if treatment is not immediate.

**Eye contact:** \* There may be irritation and pain. The vision may become blurred. The eyes may water

profusely. Corneal burns may occur. May cause permanent damage.

Ingestion: \* Corrosive burns may appear around the lips. Blood may be vomited. There may be

bleeding from the mouth or nose. It is unlikely that this substance will be swallowed due

to its physical properties.

Inhalation: \* There may be irritation of the throat with a feeling of tightness in the chest. There may

be drowsiness, slurred speech, muscular weakness, muscle twitching, tremor, blurred

vision, dilated pupils and shock.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure. Drowsiness or mental

confusion may occur.

Other information: Not applicable.

### **Section 12: Ecological information**

## 12.1. Toxicity

### **Hazardous ingredients:**

#### **SODIUM LAURYL SARCOSINATE**

| Daphnia magna                 | 48H EC50 | 29.7 | mg/l |
|-------------------------------|----------|------|------|
| ZEBRAFISH (Brachydanio rerio) | 96H LC50 | 107  | mg/l |

## 12.2. Persistence and degradability

Persistence and degradability: The biodegradability of the surfactants contained in this product are in accordance with

the requirements of the EU Detergent Regulation (EC/648/2004). Biodegradable.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

EASY FOAM (600ML) {FROM EXP 28082018}

Page: 8

12.4. Mobility in soil

Mobility: Readily absorbed into soil. Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Recycling/reclamation of metals and metal compounds. Recovery of components used

for pollution abatement.

Waste code number: 16 03 03

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

#### **Section 14: Transport information**

### 14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

#### 14.4. Packing group

# 14.5. Environmental hazards

**Environmentally hazardous:** No **Marine pollutant:** No

# 14.6. Special precautions for user

**Special precautions:** No special precautions.

Tunnel code: D

Transport category: 1

IMDG seg. group: 18

## **Section 15: Regulatory information**

EASY FOAM (600ML) {FROM EXP 28082018}

Page: 9

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Regulation (EC) No 1272/2008 of the European Parliament and of the

Council of the 16th December 2008 on Classification, labeling and packaging of Substances and Mixtures. The biodegradability of the surfactants contained in this product are in accordance with the requirements of the EU Detergent Regulation

(EC/648/2004).

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

### **Section 16: Other information**

#### Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H223: Flammable aerosol.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H330: Fatal if inhaled.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.