



# EVO-STIK MITRE ADHESIVE

Supplementary Precautionary Statements	P501	Dispose of contents/container in accordance with local regulations.
	P262	Do not get in eyes, on skin, or on clothing.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P332+313	If skin irritation occurs: Get medical advice/attention.
	P362	Take off contaminated clothing and wash before reuse.
	P321	Specific treatment (see medical advice on this label).
	P402+404	Store in a dry place. Store in a closed container.
	P403+233	Store in a well-ventilated place. Keep container tightly closed.
Supplemental label information	EUH202	Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

## 2.3. Other hazards

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2. Mixtures

ETHYL 2-CYANOACRYLATE	60-100%
CAS-No.: 7085-85-0	EC No.: 230-391-5
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335	Classification (67/548/EEC) Xi;R36/37/38

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: FIRST AID MEASURES

## 4.1. Description of first aid measures

Inhalation

Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. Get medical attention.

Ingestion

DO NOT induce vomiting. Get medical attention immediately.

Skin contact

Remove affected person from source of contamination. Promptly wash contaminated skin with water. Promptly remove clothing if soaked through and wash the skin with water. Get medical attention promptly if symptoms occur after washing.

Eye contact

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

## 4.3. Indication of any immediate medical attention and special treatment needed

### SECTION 5: FIREFIGHTING MEASURES

## 5.1. Extinguishing media

Extinguishing media

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

## 5.2. Special hazards arising from the substance or mixture

## 5.3. Advice for firefighters

### SECTION 6: ACCIDENTAL RELEASE MEASURES

# EVO-STIK MITRE ADHESIVE

## 6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact. Ensure adequate ventilation. Wear personal protective equipment. Wear self contained breathing apparatus.

## 6.2. Environmental precautions

Prevent entry into drains and water courses.

## 6.3. Methods and material for containment and cleaning up

Provide ventilation and confine spill. Do not allow runoff to sewer. Clean-up personnel should use respiratory and/or liquid contact protection. ABSORB. Absorb in vermiculite, dry sand or earth and place into containers.

## 6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Avoid spilling, skin and eye contact.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

Storage Class

Chemical storage.

### 7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ETHYL 2-CYANOACRYLATE	WEL			0.3 ppm	1.5 mg/m3	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

Protective equipment



Engineering measures

Well-ventilated area.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand protection

Use protective gloves. Use protective gloves made of: Nitrile. Use thin cotton gloves inside the rubber gloves if allergy risk.

Eye protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station.

# EVO-STIK MITRE ADHESIVE

## Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Clear
Odour	Pungent.
Solubility	Insoluble in water Polymerises in water
Relative density	1.08
Viscosity	1500 cP
Flash point (°C)	> 85

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### Inhalation

Irritating to respiratory system.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting.

#### Skin contact

Irritating to skin. Product has a defatting effect on skin.

#### Eye contact

Irritating to eyes. Spray and vapour in the eyes may cause irritation and smarting.

## SECTION 12: ECOLOGICAL INFORMATION

#### Ecotoxicity

Not regarded as dangerous for the environment. However, contamination of the aquatic or terrestrial environments should be avoided

### 12.1. Toxicity

No data available

### 12.2. Persistence and degradability

## EVO-STIK MITRE ADHESIVE

### Degradability

There are no data on the degradability of this product.

### 12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

No data available

### 12.6. Other adverse effects

Not available.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

## SECTION 14: TRANSPORT INFORMATION

General

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

### 14.1. UN number

Not applicable.

### 14.2. UN proper shipping name

Not applicable.

### 14.3. Transport hazard class(es)

Transport Labels

No transport warning sign required.

### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

### 14.6. Special precautions for user

Not applicable.

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

# EVO-STIK MITRE ADHESIVE

## Guidance Notes

Workplace Exposure Limits EH40. CHIP for everyone HSG(108). Introduction to Local Exhaust Ventilation HS(G)37.

## EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

## 15.2. Chemical Safety Assessment

### SECTION 16: OTHER INFORMATION

#### General information

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

#### Information Sources

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

#### Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision. This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

Issued By Approved EC

Revision Date Dec 2014

Revision 5

Date May 2008

#### Risk Phrases In Full

R36/37/38 Irritating to eyes, respiratory system and skin.

#### Hazard Statements In Full

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.



# EVO-STIK MITRE ADHESIVE ACTIVATOR AEROSOL

P251	Pressurized container: Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing vapour/spray.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P332+313	If skin irritation occurs: Get medical advice/attention.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container in accordance with local regulations.
Supplementary Precautionary Statements	
P264	Wash contaminated skin thoroughly after handling.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337+313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

## 2.3. Other hazards

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50C. Do not pierce or burn even after use. Do not spray on a naked flame or any incandescent material - NO SMOKING.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

BUTANE	5-10%
CAS-No.: 106-97-8	EC No.: 203-448-7
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12
HEXANE-norm	1-5%
CAS-No.: 110-54-3	EC No.: 203-777-6
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) F;R11 Repr. Cat. 3;R62 Xn;R48/20,R65 Xi;R38 R67 N;R51/53
ISOPENTANE	< 1%
CAS-No.: 78-78-4	EC No.: 201-142-8
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) F+;R12 Xn;R65 R66 R67 N;R51/53



# EVO-STIK MITRE ADHESIVE ACTIVATOR AEROSOL

N,N-DIMETHYL-PARA-TOLUIDINE		< 1%
CAS-No.: 99-97-8	EC No.: 202-805-4	
Classification (EC 1272/2008) Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT RE 2 - H373 Aquatic Chronic 3 - H412	Classification (67/548/EEC) T;R23/24/25 R33 R52/53	
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT, <0.1% BENZENE,		60-100%
CAS-No.: 64742-49-0	EC No.:	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R65. Xi;R38. F;R11. N;R51/53. R67.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

Inhalation

Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. Get medical attention.

Ingestion

DO NOT induce vomiting. Get medical attention immediately.

Skin contact

Promptly flush contaminated skin with soap or mild detergent and water. Promptly remove clothing if penetrated and flush the skin with water. Get medical attention if irritation persists after washing.

Eye contact

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

### 5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire.

### 5.3. Advice for firefighters

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

# EVO-STIK MITRE ADHESIVE ACTIVATOR AEROSOL

Avoid breathing vapour Wear personal protective equipment. Avoid skin and eye contact.

## 6.2. Environmental precautions

Prevent entry into drains and water courses.

## 6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

## 6.4. Reference to other sections

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

### 7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### 7.3. Specific end use(s)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BUTANE	WEL	600 ppm	1450 mg/m <sup>3</sup>	750 ppm	1810 mg/m <sup>3</sup>	
HEXANE-norm	WEL	20 ppm	72 mg/m <sup>3</sup>			
ISOPENTANE	WEL	600 ppm	1800 mg/m <sup>3</sup>			

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

Protective equipment



Engineering measures

Explosion-proof general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand protection

Protective gloves must be used if there is a risk of direct contact or splash. Use protective gloves made of: Nitrile.

Eye protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# EVO-STIK MITRE ADHESIVE ACTIVATOR AEROSOL

## 9.1. Information on basic physical and chemical properties

Appearance	Aerosol. Liquid
Colour	Colourless.
Odour	Light, paraffinic
Solubility	Insoluble in water
Relative density	0.71 @ °c
Vapour pressure	@ °c
Flash point (°C)	- 40 CC (Closed cup).
Auto Ignition Temperature (°C)	410

## 9.2. Other information

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

#### 10.2. Chemical stability

Stable under normal temperature conditions.

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.  
Direct Sunlight

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

Inhalation

May cause irritation to the respiratory system.

Ingestion

Harmful: may cause lung damage if swallowed.

Skin contact

Irritating to skin.

Eye contact

Irritating to eyes.

Route of entry

Inhalation.

### SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

# EVO-STIK MITRE ADHESIVE ACTIVATOR AEROSOL

## 12.4. Mobility in soil

## 12.5. Results of PBT and vPvB assessment

## 12.6. Other adverse effects

### SECTION 13: DISPOSAL CONSIDERATIONS

#### General information

This material is classified as special waste as defined by Special Waste Regulations 1996 and must be disposed of by an authorised contractor

#### 13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

### SECTION 14: TRANSPORT INFORMATION

#### 14.1. UN number

UN No. (ADR/RID/ADN)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

#### 14.2. UN proper shipping name

Proper Shipping Name                      AEROSOLS (NAPHTHA (PETROLEUM), HYDROTREATED LIGHT, <0.1% BENZENE, )

#### 14.3. Transport hazard class(es)

ADR/RID/ADN Class	2.1
ADR/RID/ADN Class	Class 2: Gases
ADR Label No.	2.1
IMDG Class	2.1
ICAO Class/Division	2.1
Transport Labels	



#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant



#### 14.6. Special precautions for user

# EVO-STIK MITRE ADHESIVE ACTIVATOR AEROSOL

EMS F-D, S-U  
Tunnel Restriction Code (D)

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

### SECTION 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

##### Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

##### Guidance Notes

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

##### EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

#### 15.2. Chemical Safety Assessment

### SECTION 16: OTHER INFORMATION

##### General information

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

##### Information Sources

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

##### Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision. This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

Issued By Approved EC

Revision Date Dec 2014

Revision 7

Date December 2003

##### Risk Phrases In Full

R33	Danger of cumulative effects.
R12	Extremely flammable.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable
R38	Irritating to skin.
R62	Possible risk of impaired fertility.
R66	Repeated exposure may cause skin dryness or cracking.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

## EVO-STIK MITRE ADHESIVE ACTIVATOR AEROSOL

### Hazard Statements In Full

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs <<Organs>> through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.