



### Model Number

NJ5-18GK50-A2

### Features

- 5 mm flush

### Accessories

#### BF 18

Mounting flange, 18 mm

#### EXG-18

Quick mounting bracket with dead stop

## Technical Data

### General specifications

Switching element function		PNP	NO/NC
Rated operating distance	$s_n$	5 mm	
Installation		flush	
Output polarity		DC	
Assured operating distance	$s_a$	0 ... 4.05 mm	
Reduction factor $r_{Al}$		0.4	
Reduction factor $r_{Cu}$		0.35	
Reduction factor $r_{304}$		0.7	

### Nominal ratings

Installation conditions			
A		0 mm	
B		0 mm	
C		15 mm	
Operating voltage	$U_B$	10 ... 60 V	
Switching frequency	f	0 ... 500 Hz	
Hysteresis	H	typ. 8 %	
Reverse polarity protection		reverse polarity protected	
Short-circuit protection		pulsing	
Voltage drop	$U_d$	$\leq 3$ V	
Operating current	$I_L$	0 ... 400 mA	
Lowest operating current	$I_m$	0 mA	
Off-state current	$I_r$	0 ... 0.5 mA typ. 0.01 mA	
No-load supply current	$I_0$	$\leq 15$ mA	
Switching state indicator		all direction LED, yellow	

### Functional safety related parameters

MTTF <sub>d</sub>	1140 a
Mission Time (T <sub>M</sub> )	20 a
Diagnostic Coverage (DC)	0 %

### Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
Storage temperature	-40 ... 85 °C (-40 ... 185 °F)

### Mechanical specifications

Connection type	cable PVC, 2 m
Core cross-section	0.5 mm <sup>2</sup>
Housing material	PBT
Sensing face	PBT
Degree of protection	IP67


### Compliance with standards and directives

Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007

### Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	Certified by China Compulsory Certification (CCC)

## Dimensions



## Electrical Connection

