

2 Core Unscreened Cable



Application

Power supply wire, suitable for indoor small electrical instrument, or general in portable tool

Construction

Conductor

Material : Stranded plain annealed copper wire

Insulation

Material : PVC

Colours : Blue and brown

Sheath

Material : PVC

Physical Properties

Operating Temperature : -15°C to 70°C

Electrical Properties


Voltage Test : Core to core : 1,500 V ac / 1 min

Voltage Rating : 300/500 V

Specification Table

Conductor Stranding	Insulation Nominal Inner Diameter	Sheath Nominal Outer Diameter	Sheath Colour	Min. Bend Radius	Nominal DC Resistance	Current Rating
32/0.2mm (1mm ²)	2.5mm	3.9mm × 6.4mm	Any	39mm	19.5Ω/km	10A

Diagram



Part Number Table

Description	Part Number
Cable, Flex, 3192Y, White, 1mm, 100m	3192Y-1MMWHT100M
Cable, Flex, 3192Y, Black, 1mm, 100m	3192Y-1MMBLK100M

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.