



PLUVEX LED UV Exposure Unit



The Pluvex Ultra Violet UV exposure unit is a high quality British built UV unit that has been designed for use in the preparation of Photosensitive materials for many industries including:-

- Production of Photo Resist PCB's ie Fortex Microtrak Pre sensitised Board
- Hot Foil Polymer Plates
- Dry Film PhotoResist Letterpress Polymer Plates Cyanotype Printing etc
- Pad Printing Plates (Clichés)
- Sandblasting Stencils
- Glass etching Stencils or Rubber Stamps etc

The Pluvex UV exposure unit is a high quality pressure contact UV exposure unit featuring UV LED Lamps in the lid to aid artwork registration. To perform an exposure, the artwork and UV sensitive material being exposed are placed on the precision exposure foam pressure pad. The separate hinged frame containing 4mm glass is then lowered on to this foam pad. It hinges from the rear of the unit and induces a progressive contact line across the face of the foam pad aiding the expulsion of air between the artwork and UV sensitive material.



FORTEX

The frame is then secured with the two front mounting catches to achieve the necessary pressure for the required artwork contact. When the frame is secured the final position and registration of the artwork is checked before lowering the exposure head and commencing the exposure. Exposure is controlled by a programmable 0-999 second digital timer that is set via touch keys.

The set time counts down during exposure and a red indicator show that the exposure is complete. The UV LED Lamps in the exposure head are screened with a special membrane which protects the operative from the potential hazards of live electrical parts. The foam exposure pad sits in a tray and can be easily removed for cleaning or quick installation of exposure trays for non-contact curing. The Pluvex is supplied with an IEC socket with integral rocker switch and moulded IEC lead and plug.

- Exposure area 355 x 254mm
- 42 x LED UV Lamps
- Glass plate with high UV transparency for UV-A transmission
- Easy alignment feature with LED Lamps in the lid
- All metal construction with Steel case
- Peak wavelength 350-400nm
- Mains on/off switch and indicator
- Mains cable and plug
- 100-240VAC 50/60Hz 15 Watts Power Consumption
- Weight 11Kg
- Dimensions of unit 500 x 440 x 150mm
- **Fortex type PLUVEX-LED**

