

PIN BUSBAR, 1PHASE 10SQMM, 56PINS, ISOLATION  
GREY CAN BE CUT, WITHOUT END CAPS




Figure similar

Model		
product brand name		SENTRON
Product designation		Pin busbar
<b>Design of the product</b>		1PH 10mm <sup>2</sup> ,56PINS GR
<b>Busbar design</b>		laminated

General technical data		
<b>Surface processing / tin-plated</b>		No

Main circuit		
Operating current / Rated value	A	63

Product details		
Product property / flexible		Yes

Mechanical Design		
<b>Width</b>	mm	5.6
<b>Length</b>	mm	990
Thickness / of busbar	mm	10.5
Material / of the busbar		SF-Cu F 24

<b>General Product Approval</b>	<b>other</b>
---------------------------------	--------------



[other](#)

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5ST3764>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/5ST3764/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**


[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=5ST3764](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5ST3764)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://ausschreibungstexte.siemens.com/tiplv>



<sup>1)</sup> Pin spacings in MW (Modular widths, 1 MW = 18 mm).

last modified:

11.03.2015