

Product type designation

RF610T transponder

SIMATIC RF610T SPECIAL VERSION ISO CARD;PVC; 86 X 54 X 0.4 MM ATEX ZONE 2/22 ISO 18000-6C, EPC CLASS 1 GEN 2 FREQUENCY 860 UP TO 928 MHZ CHIP TYPE, NXP G2XM EPC 240 BIT 64 BYTE ADD-ON MEMORY -25 UP TO +85 DGR/C; MINIMAL ORDER QUANTITY 1000 PCS



Figure similar

Wireless frequencies

Operating frequency	860 ... 960 MHz
---------------------	-----------------

Electrical data

Range / maximum	5 m; observe system manual RF600: overrange is possible, range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
Protocol / with radio transmission	EPCglobal Class 1 Gen 2 / ISO 18000-6C
Transfer rate / with radio transmission / maximum	320 kbit/s
Product property / multitag-capable	Yes
Polarization	Linear
Product component / Backup battery	No

Memory

Type of memory	EEPROM
Storage capacity / of the user memory	64 byte
Type of memory organization	EPC memory 96/240 bits, user memory 64 bytes (512 bits), TID memory 8 bytes
Number of read cycles / at ambient temperature < 40 °C / maximum	100000000000000
Number of write cycles / at ambient temperature < 40 °C / maximum	100000
Data retention time / at ambient temperature < 40 °C / not less than	10 y
Property of memory	lock, unlock, write protection, password protection
Type of transponder chip used	NXP G2XM

Mechanical data	
Material	PVC, food-safe
Color	white
Mounting distance / relating to metal surfaces / recommended / minimum	3 mm

Permitted ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> during read/write access 	-25 ... +85 °C
<ul style="list-style-type: none"> outside the read/write area 	-40 ... +85 °C
<ul style="list-style-type: none"> during storage 	-40 ... +85 °C
Protection class IP	IP67
Shock resistance	According to DIN EN 60721-3-7 Class 7 M3
Shock acceleration	1000 m/s ²
Resistance against vibration	500 m/s ²
Resistance to mechanical stress	Torsion and bending stress conditionally permissible

Design, dimensions and weight	
Width	54 mm
Height	0.4 mm
Depth	86 mm
Net weight	3 g
Mounting type	gluing, cable tie, screwing

Product properties, functions, components / general	
Product property	
<ul style="list-style-type: none"> printable 	Yes
Printing process	Thermal transfer process

Standards, specifications, approvals	
Certificate of suitability	Ex: II 3 G Ex ic IIB T6 to T4, II 3 D Ex ic IIIB T120°C, -25 °C < Ta < +85 °C
MTBF	1712 y

Accessories	
accessories	Fixing strap, spacer

Further Information / Internet Links	
Internet-Link	
<ul style="list-style-type: none"> to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
<ul style="list-style-type: none"> to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> to website: Information and Download Center 	http://www.siemens.com/automation/net/catalog
<ul style="list-style-type: none"> to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> to website: CAx Download Manager 	http://www.siemens.com/cax

- to website: Industry Online Support

<https://support.industry.siemens.com>

last modified:

09.03.2015