





NOTES:

1. MATERIALS AND FINISHES:
 BODY - BRASS, NICKEL PLATING
 BAYONET - ZINC DIECAST, NICKEL PLATING
 CONTACT - BRASS, GOLD PLATING
 INSULATOR - DELRIN
2. ELECTRICAL:
 A. IMPEDANCE: 75 OHM
 B. FREQUENCY RANGE: 0-2 GHz
 C. VSWR(RETURN LOSS): 1.3 (17.7 dB), MAX.
 D. DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS, MIN.
3. MECHANICAL:
 A. DURABILITY: 500 CYCLES MIN.
 B. TEMPERATURE RANGE: - 65°C to +165°C
4. CRIMPED FERRULE
 HEX CRIMP SIZE .255"
5. CRIMPED CONTACT PIN
 HEX CRIMP SIZE .388"

31-71008-1RFX		REVISIONS			
PART NO.	REV	DESCRIPTION	DATE	EGG	APPR
THIRD ANGLE PROJ.	8	BAYONET WAS BRASS	7/13/06	16157	GH



RECOMMENDED
CABLE STRIPPING DIM'S



CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: 0.5 - 5mm ±0.1mm 5 - 30mm ±0.2mm 30 - 120mm ±0.3mm ANGLES ±1°	MATERIAL	DRAWN CARRA	DATE 23-Jun-06	TITLE 3NC CRIMP PLUG	Amphenol RF Danbury CT USA, Taichung Taiwan, Shenzhen China www.amphenolrf.com
	REFERENCE	APPROVED <i>H. Gupta</i>	DATE 7/13/06	SCALE: 3/1	
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person in any manner, licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or be used by said drawings, specifications, or other data.	FINISH	CAD FILE F:\DWG\B\1121B1\59U20AWG\25\ND3G.V	DATE	SHEET 2 OF 2 DWG SIZE B CODE J 74868 REV 8	REV NO. 011121AAB52ND7F PART NO. 31-71008-1RFX