



DATA SHEET	01670XX
IEC compensating cable KPL Y XX x 1,5	valid from : 01.12.2008

Application

The compensating cables KPL Version Y XX x 1,5 mm² are multi-cored PVC insulated cables which transmit the thermoelectric voltage of PtRh/Pt thermocouples. They are for flexible use and fixed installation in dry and damp rooms with medium mechanical load. They may only be installed outdoors with UV protection and in observation of the max. permitted temperature range.

Design

Conductor	1,5 mm ² (48 x 0,20 mm)
Conductor material	RCB/SCB alloying, accuracy class 2 according IEC 60584 Positive conductor: Cu (copper) Negative conductor: CuNi (cupronickel)
Core insulation	PVC compound
Core identification	Positive conductor: orange Negative conductor: white
Core layering	Cores twisted together
Outer sheath	PVC compound, colour: orange

Electrical properties

Limiting deviation class 2 ± 60 µV (± 5,0 °C) / measuring point temperature +1000 °C

Mechanical and thermal properties

Temperature range	fixed installed: -40 °C upto + 80 °C occasional flexing: -5 °C up to +70 °C
Minimum bending radius	occasional flexing: 12 x cable diameter
Flammability	flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2

Originator: Frank Hörtnagl / PD-KL Approved: Werner Körner / TE	Document: DB0167001EN	page 1 of 1
--	----------------------------	-------------