

## UNITRONIC® LiYCY A

DB0044602  
valid from: 02.04.2014**Application**

UNITRONIC® LiYCY A is a screened data cable for low frequency applications with UL and CSA approval. The cable is intended for internal and external wiring of devices, machines and plants for export to the North American market or countries where UL-/CSA approved cables are used. It is designed for fixed installation and for conditional flexible use. It is used in dry and damp interiors but not appropriate for outside usage.

The screen provides protection against electromagnetic interferences.

Approval: UL AWM Style 2464, UL File No. E63634, CSA AWM I/II A/B 80°C, 300 V

**Design**

Design based on standard VDE 0812

Conductor	multi-wire strands of tinned copper wires
Insulation	special PVC-based compound
Core identification code	according to DIN 47100
Stranding	cores are stranded in layers, wrapping with foil on the outer layer
Screen	Braiding with tinned copper wires
Outer sheath	special PVC-based compound colour: dark grey (RAL 7005)

**Electrical properties at 20°C**

Conductor resistance	0.14 mm <sup>2</sup> 26 AWG max. 150 Ω/km
	0.23 24 94.2
	0.34 22 59.4
	0.5 20 36.7
	0.75 19 29.1
	1.0 18 23.2
	1.5 16 14.6
Specific insulation resistance	> 20 G Ω x cm
Mutual capacitance	C/C: approx. 120 nF/km
	C/S: approx. 160 nF/km (at 800 Hz)
Inductivity	approx. 0.65 mH/km
Peak working voltage	300 V (not for power applications)
Test voltage	A/A: 1500 V

**Mechanical and thermal properties**

Minimum bending radius	Flexing: 15 x cable Ø
	Fixed installation: 6 x cable Ø
Temperature range	Flexing: - 5 °C up to +70 °C
	Fixed installation: - 40 °C up to +80 °C
Flammability	flame retardant acc. to IEC 60332-1-2
	UL: FT1 and VW1
	CSA: FT1
EC directive	This cable is conform to the EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances).