

tesa® 64286

Strapping tape for basic applications

PRODUCT INFORMATION

Product Description

tesa® 64286 is a tensilized polypropylene strapping tape with a hot melt adhesive system.

tesa® 64286 exhibits a good tensile strength with low elongation at the same time. The product shows a high peel adhesion.

Main Application

- Palettizing
- Reinforcing
- · Closing of shipping cartons

Technical Data

MOPP Backing material Adhesion to steel 7.5 N/cm Total thickness 73 µm Elongation at break 40 % Type of adhesive synthetic rubber 100 N/cm Tensile strength

For latest information on this product please visit http://l.tesa.com/?ip=64286

Page 1 of 1 / As of 09/29/13

Quickbornstraße 24 20253 Hamburg

Germany Phone: +49 (40) 4909 101 http://www.tesa.com

tesa tape inc.

5825 Carnegie Boulevard Charlotte, N.C. 28209 United States of America Phone: +1 (704) 554 0707 Phone: +65 (68) 612 026

tesa tape Asia Pacific Pte. Ltd.

164 Gul Circle, Singapore 629621

Fax: +1 (704) 553 5634 Fax: +65 (68) 614 790 http://www.tesatape.com http://www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.