

# TECHNICAL DATA

Version 19

## AT160 Premium Quality Matt Waterproof Cloth Tape

### General description

A polythene extruded matt cloth tape with a waterproof finish coated with an aggressive pressure sensitive, solvent free rubber-resin adhesive.

- Very strong
- Easy tear and unwind
- Conformable to awkward shapes
- Water resistant finish
- Good abrasion resistance
- Non-corrosive adhesive
- Can be written on
- Wide colour range

### Specification

Certification\* to the following standard may be available on request.  
DEF STAN 81-145 2a.

### Technical Details

#### Typical Values

Thickness	0.33mm
Breaking Load	85 N/cm
Elongation	8%
Adhesion	
Steel	3.5 N/cm
Self	2.2 N/cm
Moisture Vapour Permeability	35g/m <sup>2</sup> /24hrs
Water extract	
PH	6.5 to 7.5
Chloride Max	0.05% as NaCl
Sulphate Max	0.25% as Na <sub>2</sub> SO <sub>4</sub>
RoHS compliant	Yes
Service Temperature	-50°C to +80°C
Application Temperature	+10°C to +45°C
Storage Temperature	+12°C to +25°C

Standard charge for certificate:£25.00.



#### NOTE

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

#### STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.



#### AFERA

Association des Fabricants Européens de Rubans  
Auto-Adhésifs.

#### Adding more to adhesive tape

Advance Tapes International Limited  
Westmoreland Avenue  
Thurmaston  
Leicester LE4 8PH  
England

Tel. +44 (0)116 251 0191  
Fax. +44 (0)116 265 2046  
contact@advancetapes.com

www.advancetapes.com

Registered in England No. 929843  
Vat No. 115-6143-00



Q05026

**Part Number Table**

Description	Part Number
AT160 PREMIUM QUALITY MATT CLOTH TAPE	AT160 WHITE 50M X 50MM
AT160 PREMIUM QUALITY MATT CLOTH TAPE	AT160 GREY 50M X 50MM
AT160 PREMIUM QUALITY MATT CLOTH TAPE	AT160 BLUE 50M X 50MM
AT160 PREMIUM QUALITY MATT CLOTH TAPE	AT160 GREEN 50M X 50MM
AT160 PREMIUM QUALITY MATT CLOTH TAPE	AT160 YELLOW 50M X 50MM
AT160 PREMIUM QUALITY MATT CLOTH TAPE	AT160 RED 50M X 50MM

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. element14 is the registered trademark of the Group. © Premier Farnell Limited 2016.