

2002-07-04

ELFA

PRODUKTINFORMATION

Vi reserverar oss mot fel samt förbehåller oss rätten till ändringar utan föregående meddelande

ELFA artikelnr


72-091-09 25TTS12 tyrist 1200V 25A

PHASE CONTROL SCR

Description/Features

The 25TTS.. **SAFEIR** series of silicon controlled rectifiers are specifically designed for medium power switching and phase control applications. The glass passivation technology used has reliable operation up to 125°C junction temperature.

Typical applications are in input rectification (soft start) and these products are designed to be used with International Rectifier input diodes, switches and output rectifiers which are available in identical package outlines.

	V_T	< 1.25V @ 16A
	I_{TSM}	= 300A
	V_{RRM}	800 to 1600V


Output Current in Typical Applications

Applications	Single-phase Bridge	Three-phase Bridge	Units
Capacitive input filter $T_A = 55^\circ\text{C}$, $T_J = 125^\circ\text{C}$, common heatsink of 1°C/W	18	22	A

Major Ratings and Characteristics

Characteristics	25TTS..	Units
$I_{T(AV)}$ Sinusoidal waveform	16	A
I_{RMS}	25	A
V_{RRM}/V_{DRM}	upto 1600	V
I_{TSM}	300	A
V_T @ 16 A, $T_J = 25^\circ\text{C}$	1.25	V
dv/dt	500	V/ μs
di/dt	150	A/ μs
T_J	-40 to 125	$^\circ\text{C}$

Package Outline



Also available in SMD-220 package (series 25TTS..S)

Voltage Ratings

Part Number	V_{RRM} , maximum peak reverse voltage V	V_{DRM} , maximum peak direct voltage V	I_{RRM}/I_{DRM} 125°C mA
25TTS08	800	800	10
25TTS12	1200	1200	
25TTS16	1600	1600	

Absolute Maximum Ratings

Parameters	25TTS..	Units	Conditions
$I_{T(AV)}$ Max. Average On-state Current	16	A	@ $T_C = 93^\circ\text{C}$, 180° conduction half sine wave
I_{RMS} Max. RMS On-state Current	25		
I_{TSM} Max. Peak One Cycle Non-Repetitive Surge Current	300 350		10ms Sine pulse, rated V_{RRM} applied 10ms Sine pulse, no voltage reapplied
I^2t Max. I^2t for fusing	450 630	A^2s	10ms Sine pulse, rated V_{RRM} applied 10ms Sine pulse, no voltage reapplied
$I^2\sqrt{t}$ Max. $I^2\sqrt{t}$ for fusing	6300		$A^2\sqrt{s}$
V_{TM} Max. On-state Voltage Drop	1.25	V	@ 16A, $T_J = 25^\circ\text{C}$
r_t On-state slope resistance	12.0	$m\Omega$	$T_J = 125^\circ\text{C}$
$V_{T(TO)}$ Threshold Voltage	1.0	V	
I_{RM}/I_{DM} Max. Reverse and Direct Leakage Current	0.5 10	mA	$T_J = 25^\circ\text{C}$ $T_J = 125^\circ\text{C}$
			$V_R = \text{rated } V_{RRM} / V_{DRM}$
I_H Holding Current	Typ. Max. -- 100 100 150	mA	Anode Supply = 6V, Resistive load, Initial $I_T = 1A$ 25TTS08, 25TTS12 25TTS16
I_L Max. Latching Current	200		Anode Supply = 6V, Resistive load
dv/dt Max. Rate of Rise of off-state Voltage	500		V/ μs
di/dt Max. Rate of Rise of turned-on Current	150	A/ μs	

Triggering

Parameters	25TTS..	Units	Conditions
P_{GM} Max. peak Gate Power	8.0	W	
$P_{G(AV)}$ Max. average Gate Power	2.0		
$+I_{GM}$ Max. peak positive Gate Current	1.5	A	
$-V_{GM}$ Max. peak negative Gate Voltage	10	V	
I_{GT} Max. required DC Gate Current to trigger	60	mA	Anode supply = 6V, resistive load, $T_J = -10^\circ\text{C}$
	45		Anode supply = 6V, resistive load, $T_J = 25^\circ\text{C}$
	20		Anode supply = 6V, resistive load, $T_J = 125^\circ\text{C}$
V_{GT} Max. required DC Gate Voltage to trigger	2.5	V	Anode supply = 6V, resistive load, $T_J = -10^\circ\text{C}$
	2.0		Anode supply = 6V, resistive load, $T_J = 25^\circ\text{C}$
	1.0		Anode supply = 6V, resistive load, $T_J = 125^\circ\text{C}$
V_{GD} Max. DC Gate Voltage not to trigger	0.25		$T_J = 125^\circ\text{C}$, V_{DRM} = rated value
I_{GD} Max. DC Gate Current not to trigger	2.0	mA	$T_J = 125^\circ\text{C}$, V_{DRM} = rated value

Switching

Parameters	25TTS..	Units	Conditions
t_{gt} Typical turn-on time	0.9	μs	$T_J = 25^\circ\text{C}$
t_{rr} Typical reverse recovery time	4		$T_J = 125^\circ\text{C}$
t_q Typical turn-off time	110		

Thermal-Mechanical Specifications

Parameters	25TTS..	Units	Conditions
T_J Max. Junction Temperature Range	-40 to 125	$^\circ\text{C}$	
T_{stg} Max. Storage Temperature Range	-40 to 125		
R_{thJC} Max. Thermal Resistance Junction to Case	1.1	$^\circ\text{C/W}$	DC operation
R_{thJA} Max. Thermal Resistance Junction to Ambient	62		
R_{thCS} Typ. Thermal Resistance Case to Heatsink	0.5		Mounting surface, smooth and greased
wt Approximate Weight	2 (0.07)	g (oz.)	
T Mounting Torque	Min.	6 (5)	Kg-cm (lbf-in)
	Max.	12 (10)	
Case Style	TO-220AC		




Fig. 1 - Current Rating Characteristics




Fig. 2 - Current Rating Characteristics




Fig. 3 - On-state Power Loss Characteristics




Fig. 4 - On-state Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-state Voltage Drop Characteristics




Fig. 8 - Gate Characteristics





Fig. 9 - Thermal Impedance Z_{thJC} Characteristics

Outline Table



Ordering Information Table

Device Code				
25	T	T	S	16
①	②	③	④	⑤

<p>1 - Current Rating, RMS value</p> <p>2 - Circuit Configuration: T = Single Thyristor</p> <p>3 - Package: T = TO-220AC</p> <p>4 - Type of Silicon: S = Converter Grade</p> <p>5 - Voltage code: Code x 100 = V_{RRM}</p>	<table border="1"> <tr><td>08 = 800V</td></tr> <tr><td>12 = 1200V</td></tr> <tr><td>16 = 1600V</td></tr> </table>	08 = 800V	12 = 1200V	16 = 1600V
08 = 800V				
12 = 1200V				
16 = 1600V				

2 (A)
1 (K) (G) 3

