INDIGA bench stone

Type 9010



Application:

For sharpening and reworking tools for wood, metal and plastic processing, e.g. scrapers, machine and plane knives, steels, reamers and gauges as well as measuring instruments.

Execution

- Best used with thin-bodied oil, petroleum or water
- Machined and wetted on all sides after burning

Advantage:

High endurance and grinding force

Art. no.	69340 215
Brand	LAPPORT
Manufacturer Part Number	100004
Binding	Ceramically bound
Surface structure	Medium
Grid size	150
Form	Rectangular
Length	100 mm
Width	25 mm
Thickness	13 mm
Number of pieces per packet	1 PCS
Material of abrasive medium	Corundum
Suitable for finishing	2 - suitable
Suitable for main machining	2 - suitable
Suitable for surface inspection	3 - less suitable
Suitable for surface care	2 - suitable
Suitable for material rubber	3 - less suitable
Suitable for material cast iron	2 - suitable
Suitable for material HSS	3 - less suitable
Suitable for material carbide	3 - less suitable
Suitable for material ceramic	3 - less suitable
Suitable for material plastics	3 - less suitable
Suitable for material non-ferrous metals	3 - less suitable
Suitable for material steel (hardened)	2 - suitable
Suitable for material steel (unhardened)	1 - very suitable
Suitable for material tool steel	2 - suitable
ISO	525
Length x width	100 x 25 mm
Length x width x thickness	100 x 25 x 13 mm
Type description	Corundum
Gross Weight	0.100 kg
Product Group	6HL



