

Technical Data Sheet	Title: 0800Water
Effective Date: March 2020	Prepared By: Sam Murphy
Issue Number: 7	Authorised By: Robin Lamb



**Product Description**

Water grade PTFE thread seal tape. (Polytetrafluoroethylene 100% Raw Polymer)

**Applications**

Commonly used in the plumbing & heating industries for sealing pipe threads such as Water and Propylene Glycol, Kerosene and Diesel.

**Features & Benefits**

- Non-adhesive no need for messy compounds
- Won't harden or dry out
- Air & watertight seal
- Impermeable to >7bar
- Resistant to cracking
- Performs a lubricating function

**Technical Performance**

Description	Units	Value
Tape thickness	mm	0.076 ±10%
Temperature	°c	-60 to +260
Density	gr/cm3	0.33
Pressure	Bar	7

**Declaration of Conformity Information**

- BS 7786:2006
- BS 6920-1:2000
- WRAS Approval 1804504 re-approval of 1306504

**REACH SVHC Status** – NO SVHC present according to candidates list of the **UK 25/06/20 & EU 19/01/21**

**RoHS Compliance Status** – Not Applicable

**Storage Details**

Shelf life indefinite stored at the moderate temperature and humidity environment.

The information supplied is accurate to the best of Bruce Douglas Marketing's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)