# ACT20JF35AE [V001] ACTIVE

### DEUTSCH | DEUTSCH 38999 Series III Composite Connectors

TE Internal #: YACT20JF35AEV00100

Standard Circular Connectors, Cable-to-Panel, 66 Position,

Sealable, Wire & Cable, Signal, Panel Mount, DEUTSCH 38999

Series III Composite Connectors

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors



Connector System: Cable-to-Panel

Number of Positions: 66

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Contact Current Rating (Max): 5 A

#### **Features**

### **Product Type Features**

Product Type	Connector
Assembly Type	Electrical Connector
Connector System	Cable-to-Panel
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Circular Connector Type	Receptacle
Shell Type	Square Flange Receptacle

## **Configuration Features**

Keying & Polarized Position Locations	E
Factory Installed Backshell	No
Keying	Keyway Polarization E
Number of Positions	66
Number of Power Positions (	0
Number of Signal Positions	66
Contacts Preloaded	No

#### **Electrical Characteristics**

Voltage 1300 Vrms	
-------------------	--



Operating Voltage	400 VAC
Body Features	
Feedthrough Type	No
Environmental Protection Type	Elastomer Sealed
Entry Style	Rear Insertion
Peripheral Seal Material	Silicone
Environmental Protection	Yes
Weight	19.7 g[.0435 lb]
O-Ring Material	Silicone
Fluid Type	Coolanol 25, M2-V, MIL-DTL-5624 (JP-4,JP-5), MIL-DTL-83133 (JP-8), MIL-PRF-23699, MIL-PRF-5606, MIL-PRF-7808, SEA-AMS1424 Type I
Shell Plating Material	Cadmium, O.D.
Shell Base Material	Composite
Circular Connector Insulation Material Type	Hard Dielectric/Silicone
Hermetically Sealed	No
Contact Features	
Contact Quantity (Size 22D)	66
Contact Current Rating (Max)	5 A
Reverse Gender	No
Contact Layout Arrangement	F35
Circular Connector Contact Type	Less Pin
Mechanical Attachment	
Mating Retention Type	Triple Start Threaded
Panel Mount Feature	With
Panel Mount Feature Type	Square Flange
Connector Mounting Type	Panel Mount
Polarization Code	E
Mating Alignment Type	Keyed
Mating Retention	With
Housing Features	
Circular Connector Shell Size	19
Alignment Keyed	Clocking



#### **Dimensions**

Accepts Wire Insulation Diameter Range	.76 – 1.37 mm[.03 – .054 in]
Assembly Length	31.5 mm[1.24 in]
Wire Size	.08 – .33 mm²

## **Usage Conditions**

Fluid Resistance	Yes
Operating Temperature Range	-65 - 200 °C[-85 - 392 °F]

## Operation/Application

Durability Rating	500 Cycles
Circuit Application	Signal
Shielded	Yes

## **Packaging Features**

Packaging Quantity	1	
--------------------	---	--

#### Other

Position Locations Omitted All
--------------------------------

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224)  Candidate List Declared Against: JUNE 2022 (224)  SVHC > Threshold:  Cd (4.1% in Plating)  Decamethylcyclopentasiloxane (D5) (5% in Insert Subassembly)  Article Safe Usage Statements:  Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

Standard Circular Connectors, Cable-to-Panel, 66 Position, Sealable, Wire & Cable, Signal, Panel Mount, DEUTSCH 38999 Series III Composite Connectors




This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



# Also in the Series | DEUTSCH 38999 Series III Composite Connectors



## Customers Also Bought









Standard Circular Connectors, Cable-to-Panel, 66 Position, Sealable, Wire & Cable, Signal, Panel Mount, DEUTSCH 38999 Series III Composite Connectors













### **Documents**

**Product Drawings** 

SQUARE FLANGE RECEPTACLE

English

Datasheets & Catalog Pages

DEUTSCH MIL-DTL-38999 Connectors Quick Reference Guide

English

12/06/2022 10:12PM | Page 5