

# RJ45 connector - CUC-V14-C1ZNI-T/R4E8 - 1422663

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Push-pull connector (version 14), die-cast zinc, with RJ45 connector insert, 8-pos., with IDC fast connection technology, for 1 and 7-wire cores, 26 ... 24 AWG, for cable diameter of 5.5 mm ... 10 mm

## Why buy this product

- ✓ Push-pull ADVANCE connector
- ✓ Locking system to prevent inadvertent removal
- ✓ Protected data transmission, thanks to 360° shielding concept
- ✓ High resistance to ESD and EMC for reliable transmission

## Ethernet

### Key Commercial Data

|                                      |               |
|--------------------------------------|---------------|
| Packing unit                         | 1 STK         |
| GTIN                                 |               |
| GTIN                                 | 4055626311326 |
| Weight per Piece (excluding packing) | 109.300 g     |
| Sales Key                            | ABNEAA        |

## Technical data

### Mechanical characteristics

|                              |  |
|------------------------------|--|
| Number of positions          | 8  |
| Connection profile           | RJ45   |
| Locking type                 | Push Pull  |
| Insertion/withdrawal cycles  | ≥ 750  |
| Connection method            | IDC fast connection                                      |
| Conductor cross section      | 0.14 mm <sup>2</sup> ... 0.23 mm <sup>2</sup> (solid)    |
|                              | 0.14 mm <sup>2</sup> ... 0.25 mm <sup>2</sup> (stranded) |
| Connection cross section AWG | 26 ... 24 (solid)  |
|                              | 26 ... 24 (stranded)                                     |
| Max. cable diameter          | 5.5 mm ... 10 mm   |
| External cable diameter      | 5.5 mm ... 10 mm   |
| Cable outlet                 | angled   |

# RJ45 connector - CUC-V14-C1ZNI-T/R4E8 - 1422663

## Technical data

### Mechanical characteristics

|                      |            |
|----------------------|------------|
| Degree of protection | IP65/IP67  |
| Type                 | Version 14 |
| No. of cable outlets | 1          |

### Ambient conditions

|   |                  |
|---|------------------|
| Ambient temperature (operation)         | -40 °C ... 70 °C |
| Ambient temperature (assembly)          | -10 °C ... 40 °C |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |

### Material data

|                          |               |
|--------------------------|---------------|
| Housing material         | Zinc die-cast |
| Housing surface material | Nickel-plated |
| Seal material            | NBR           |
| Height                   | 50 mm         |

### Electrical characteristics

|   |                       |
|---|-----------------------|
| Rated current                           | 1.75 A                |
| Frequency range                         | to 100 MHz            |
| Transmission characteristics (category) | CAT5 (IEC 11801:2002) |

### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27261204 |
| eCl@ss 7.0 | 27440205 |
| eCl@ss 8.0 | 27440101 |
| eCl@ss 9.0 | 27440101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 5.0 | EC002636 |
| ETIM 6.0 | EC002636 |

## Accessories

### Accessories

## RJ45 connector - CUC-V14-C1ZNI-T/R4E8 - 1422663

### Accessories

#### Panel mounting frame

Panel mounting frames - CUC-V14-F1ZNI-EM/R4F8 - 1413961



RJ45 panel mounting frame, IP67, for push-pull interlocking, metal, for rectangular mounting cutout, with seal and mounting screws, incl. RJ45 insert with IDC cable connection

---

Panel mounting frames - CUC-V14-F1ZNI-EM/R4B8 - 1413962



RJ45 panel mounting frame, IP67, for push-pull interlocking, metal, for rectangular mounting cutout, with seal and mounting screws, incl. RJ45 coupling module

---

Panel mounting frames - CUC-V14-F1ZNI-EM/R4O - 1413963



RJ45 panel mounting frame, IP67, for push-pull interlocking, metal, for PCB connection, for square panel cutout, with grommet and mounting screws

---

#### Protective cover

Protective covers - VS-PPC-F1-PC-POBK - 1405316



Protective cover, IP65, with push-pull locking for covering the contact insert in the push-pull connector for RJ45 and SC-RJ, plastic

---

Stripping tool - VS-CABLE-STRIP-VARIO - 1657407



Stripping tool, for the multi-level stripping of shielded cables

---

