

Filter attachment

With fan and exhaust air control, for safety cabinet no. 50069002-012



Application:

For ventilating and monitoring safety cabinets by filtering almost 100% of harmful solvents (hydrocarbons) via molecular adsorption. The filtering provides optimum protection for the user. No need for an additional exhaust air connection. The purified air is released into the ambient air.

Version:

- Sheet steel housing in silver with pearl-mica effect
- Integrated LED error indicator
- Plug and play: simply connect to a 230-V/50-Hz power supply using the CEE 7/7 plug
- Built-in fan in accordance with DIN EN 14986
- Removable activated carbon filter element (2 kg fill content)
- Removable particle filter in accordance with DIN EN 779.
- Filter performance (activated carbon): 30% of the filling quantity for all media of the supplied materials list.
- Visual and audible alarm in the event of faults.
- One dry contact (24 V/2 A).
- Conformity of the manufacturer according to ATEX Guideline RL94/9EC and Low Voltage Directive 2006/95/EC

Advantage:

- Multi-stage filter system with safety factor 2
- Filter warning system
- Quiet fan
- Plug and play for easy installation



Art. no.	50069 400
Width	415 mm
Height	310 mm
Material	Sheet steel
Surface	Powder-coated/ steel plate

EAN-Code

4036361097171